



PRODUCT DATA SHEET

Power Lube® Industrial High Performance Lubricant
w/PTFE, 11 Wt Oz
No. 03045



Product Description

POWER LUBE is a high performance, multi-purpose lubricant that utilizes PTFE and extreme pressure additives to provide unparalleled lubricating performance. It has twice the load carrying capacity of most general purpose lubricants.

Applications

Bearings, gears, linkages, motors, chains, cables, rollers, guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

High Performance Lubricant with PTFE

Net Fill

11 Wt Oz

UPC Code

078254030456

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.1H x 8.3W x 11.1D in

Cases Per Pallet

133

Case Weight

10 lbs

I 2 of 5 Code

30078254030457

Appearance

Light Amber Liquid w/white precipitate

Base Type

Petroleum Solvent

Flash point (F)

<20°F

Flash point (C)

<-7°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.863

Plastic Safe

No

Film Type

Wet

Film Thickness

Not Determined

Last revised: 5/4/2016
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Evaporation Rate	Fast
Dielectric Strength	Not Determined
Working Temp (F)	Max 300°F
Working Temp (C)	Max 148.9°C
Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	017403
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	23.9
VOC g/L (Federal)	206.3
VOC Lbs./Gal. (Federal)	1.7
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum solvents or mineral spirits.

Last revised: 5/4/2016
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.