

PRODUCT DATA SHEET

Cutting Oil Thread Cutting Lubricant, 12 Wt Oz No. 14050

Product Description

Unit Package Description

Applications

ng Oil ead Cutting **Ubricant**

ubricante de aceite de conte de tornillos roscados

^{te en Ferrous & Non-Ferrous Metals ^{Tes le} Vertical Surfaces} ⁷aa uliizar en Metales Ferrosos V **TTASAS** ^{le Achiere} a Superficies Verticales



Brand **Generic Description 1** Net Fill **UPC** Code Unit Dimensions Units Per Case **Case Dimensions** Cases Per Pallet Case Weight I 2 of 5 Code Appearance Base Type Flash point (F) Flash point (C) Flammability Class - CPSC Spec Gravity Concentrate Plastic Safe Film Type **Evaporation Rate** Working Temp (F) Working Temp (C) Propellant

Cutting Oil is a superior thread cutting lubricant for use on all types of metals, including brass, copper and aluminum.


Tapping, threading, drilling, sawing, shearing, turning, and reaming metal parts, pipes, conduit, screws, bolt holes, housings, aluminum sheets, strapping, gears and chains.

16 Ounce Aerosol CRC Thread Cutting Lubricant 12 Wt Oz 078254140506 7.75H x 2.63W x 2.63D in 12 8.1H x 8.3W x 11.1D in 133 12 lbs 30078254140507 **Brown Liquid** Petroleum $> 300^{\circ} F$ >149°C Flammable 0.924 Safe on Acrylic Plastics Non-Drying Slow Max 300°F Max 148.9°C Hydrocarbon

> Last revised: 5/4/2016 Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



of CRC Industries, Inc.

and adheres to the strictest guidelines for quality in all facets of research, development and production. CRC*, K&W*, Sta-Lube*, Marykate* and products denoted with * and ™ are trademarks

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair



PRODUCT DATA SHEET

NSF Category Code	P1
NSF Number	017206
Aerosol Flammability Level	111
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	20
VOC g/L (Federal)	184.8
VOC Lbs./Gal. (Federal)	1.54
VOC Category	Cutting or Tapping Oil (Aerosol)
Restricted from Sale In:	SCAQMD
Removal (How To)	Remove with general purpose degreaser.

CRC

Cutting Oil Thread Cutting Lubricant

lubricante de aceite de corte de tornillos roscados


te el Ferrous & Non-Ferrous Metals Cago le Vertical Surfaces Para allizar en Metales Ferrosos V la firmases la Achiere a Superficies Verticales



Last revised: 5/4/2016 Page 2 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC*, K&W*, Sta-Lube*, Marykate* and products denoted with * and ™ are trademarks

of CRC Industries, Inc.