



## PRODUCT DATA SHEET

Safety Anti-Slip Paint Transparent, 12 Wt Oz  
No. 18024



### Product Description

Anti-Slip Coating which produces a slip resistant coating which is resistant to oil, gas, and most chemicals. Use as a finish coat and recoat every 2-4 months based on traffic.

### Color

Clear

### Applications

Interior and exterior use on wood, metal, concrete, asphalt, railings, stairs, tools, boat docks, ramps etc.

### Unit Package Description

16 Ounce Aerosol

### Brand

CRC

### Generic Description 1

Slip Resistant Coating

### Net Fill

12 Wt Oz

### UPC Code

078254180243

### Unit Dimensions

7.75H x 2.63W x 2.63D in

### Units Per Case

6

### Case Dimensions

8.25H x 5.75W x 8.25D in

### Cases Per Pallet

152

### Case Weight

6 lbs

### I 2 of 5 Code

30078254180244

### Appearance

Gritty Beige Liquid

### Flash point (F)

-4°F

### Flash point (C)

25°C

### Flammability Class - CPSC

Extremely Flammable

### Spec Gravity Concentrate

0.8

### Plastic Safe

No

### Evaporation Rate

>1 (butyl acetate=1)

### Dry Time - Fully Dry

24 Hours

### Dry Time - Tack Free

10 Minutes

### Recoat

30 Minutes

### Coverage

~7 Sq Ft

Last revised: 2/27/2017  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	50 to 90°F
Working Temp (C)	10 to 32°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Not Determined
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	45.5
VOC g/L (Federal)	535
VOC Lbs./Gal. (Federal)	4.46
VOC Category	Aerosol Coating: Slip-Resistant Coating
MIR Limit (EPA)	2.45
MIR Limit (CA)	2.1
MIR Value	1.47
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.

Last revised: 2/27/2017  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.