



PRODUCT DATA SHEET

Good Grip® Black Anti-Slip Paint, 12 Wt Oz
No. 18026



Product Description

Anti-Slip Coating which produces a slip resistant coating which is resistant to oil, gas, and most chemicals. Use as a finish coat and recoat every 2-4 months based on traffic.

Color

Black

Applications

Interior and exterior use on wood, metal, concrete, asphalt, railings, stairs, tools, boat docks, ramps etc.

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Slip Resistant Coating

Net Fill

12 Wt Oz

UPC Code

078254180267

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

6

Case Dimensions

8.25H x 5.75W x 8.25D in

Cases Per Pallet

152

Case Weight

6 lbs

I 2 of 5 Code

30078254180268

Appearance

Gritty Black Liquid

Flash point (F)

-4°F

Flash point (C)

25°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.8

Plastic Safe

No

Evaporation Rate

>1 (butyl acetate=1)

Dry Time - Fully Dry

24 Hours

Dry Time - Tack Free

10 Minutes

Recoat

30 Minutes

Coverage

~7 Sq Ft

Last revised: 3/7/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (F)	50 to 90°F
Working Temp (C)	10 to 32°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Not Determined
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	46.6
VOC g/L (Federal)	546.3
VOC Lbs./Gal. (Federal)	4.56
VOC Category	Aerosol Coating: Slip-Resistant Coating
MIR Limit (EPA)	2.45
MIR Limit (CA)	2.1
MIR Value	1.28
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.

Last revised: 3/7/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with * and ™ are trademarks of CRC Industries, Inc.