



# PRODUCT DATA SHEET

Upside Down Marking Paints-Red Fluorescent, 17 Wt Oz  
No. 18207

## Product Description

Clearly and effectively marks the location of underground utilities. Colors meet the A.P.W.A. One Call International Color Standards. Safe to use on turf grass, fields, and golf courses.

## Color

Red Fluorescent

## Applications

To identify and code surfaces such as metal, concrete, asphalt, gravel, soil, trees and grass for construction, utility, recreational, municipal and landscaping sites, golf courses, nurseries and surveying.

## Unit Package Description

20 Ounce Aerosol

## Brand

CRC

## Generic Description 1

Upside Down Marking Paints

## Net Fill

17 Wt Oz

## UPC Code

078254182070

## Unit Dimensions

9.25H x 2.63W x 2.63D in

## Units Per Case

6

## Case Dimensions

10H x 5.75W x 8.25D in

## Cases Per Pallet

152

## Case Weight

8 lbs

## I 2 of 5 Code

30078254182071

## Appearance

Red Fluorescent Liquid

## Flash point (F)

-2°F

## Flash point (C)

-19&#176;C

## Flammability Class - CPSC

Extremely Flammable

## Spec Gravity Concentrate

0.77 to 0.85

## Plastic Safe

Yes

## Dry Time - Fully Dry

1 Hour

## Dry Time - Tack Free

30 Minutes

## Coverage

0 to 700 Linear Feet

## Propellant

Hydrocarbon



Last revised: 2/13/2017  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET

Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Federal)	50.5
VOC g/L (Federal)	524.7
VOC Lbs./Gal. (Federal)	4.38
VOC Category	Aerosol Coating: Ground Traffic/Marking
MIR Limit (EPA)	1.2
MIR Limit (CA)	0.85
MIR Value	0.57
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.



Last revised: 2/13/2017  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.