




UN874035104/10 | CS44P BLU C6A 4/23 U/UTP RL 1KFT
CS44P ETL Verified Category 6A U/UTP Cable, plenum, blue jacket, 4 pair count, 1000 ft (305 m) length reel

Product Classification

| | |
|-----------------------|--------------------|
| Portfolio | Uniprise® |
| Product Type | Twisted pair cable |
| Regional Availability | North America |

Cross Section Drawing



Construction Materials

| | |
|---------------------|-------------|
| Jacket Material | PVC |
| Conductor Material | Bare copper |
| Insulation Material | FEP |
| Separator Material | Polyolefin |

Dimensions

| | |
|----------------------|---------------------|
| Cable Length | 305 m 1000 ft |
| Cable Weight | 42.40 lb/kft |
| Diameter Over Jacket | 7.239 mm 0.285 in |
| Jacket Thickness | 1.295 mm 0.051 in |

Electrical Specifications

| | |
|----------------------------------|-----|
| ANSI/TIA Category | 6A |
| dc Resistance Unbalance, maximum | 4 % |

UN874035104/10 | CS44P BLU C6A 4/23 U/UTP RL 1KFT

| | |
|---------------------------------------|--|
| dc Resistance, maximum | 7.61 ohms/100 m |
| Mutual Capacitance | 6.0 nF/100 m @ 1 kHz |
| Nominal Velocity of Propagation (NVP) | 66 % |
| Operating Frequency, maximum | 500 MHz |
| Transmission Standards | ANSI/TIA-568-C.2 ISO/IEC 11801 Class EA |
| Safety Voltage Rating | 300 V |
| Dielectric Strength, minimum | 1500 Vac 2500 Vdc |
| Note | Consult ANSI/TIA-568-C.2 Annex G for length de-rating guidance for cable installation in higher temperature environments |

Environmental Specifications

| | |
|--------------------------|-------------------------------------|
| Environmental Space | Plenum |
| ETL Temperature Rating | 75 °C 167 °F |
| Flame Test Method | CMP |
| Installation Temperature | 0 °C to +60 °C (+32 °F to +140 °F) |
| Operating Temperature | -20 °C to +75 °C (-4 °F to +167 °F) |

General Specifications

| | |
|--------------------------|--------------------|
| Cable Type | U/UTP (unshielded) |
| Packaging Type | Reel |
| Pairs, quantity | 4 |
| Cable Component Type | Horizontal |
| Jacket Color | Blue |
| Product Number | CS44P |
| Brand | Uniprise® |
| Conductor Gauge, singles | 23 AWG |
| Conductor Type, singles | Solid |
| Conductors, quantity | 8 |
| Separator Type | Bisector |

Mechanical Specifications

| | |
|--------------------------|---------------|
| Pulling Tension, maximum | 11 kg 25 lb |
|--------------------------|---------------|

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2011/65/EU | Compliant |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |



Electrical Performance

| | |
|--------|---|
| Std | Refers to the standard value listed under Transmission Standards in the Electrical Specifications above |
| Typ | Typical |
| IL | Insertion Loss (dB/100m) |
| NEXT | Near End Crosstalk (dB/100m) |
| ACR | Attenuation to Crosstalk Ratio (dB/100m) |
| PSNEXT | Power Sum Near End Crosstalk (db/100m) |
| PSACR | Power Sum Attenuation to Crosstalk Ratio (dB/100m) |
| ACRF | Attenuation to Crosstalk Ratio - Far End (dB/100m) |
| PSACRF | Power Sum Attenuation to Crosstalk Ratio – Far End (dB/100m) |
| RL | Return Loss (dB) |

| Freq. MHz | IL | | NEXT | | ACR | | PSNEXT | | PSACR | | ACRF | | PSACRF | | RL | |
|-----------|------|------|------|------|-------|------|--------|------|-------|------|------|------|--------|------|------|------|
| | Std | Typ | Std | Typ | Std | Typ | Std | Typ | Std | Typ | Std | Typ | Std | Typ | Std | Typ |
| 1 | 2.1 | 1.8 | 74.3 | 90.6 | 72.2 | 88.8 | 72.3 | 88.3 | 70.2 | 86.5 | 67.8 | 82.1 | 64.8 | 80.3 | 20.0 | 32.2 |
| 4 | 3.8 | 3.6 | 65.3 | 82.4 | 61.5 | 78.8 | 63.3 | 80.2 | 59.5 | 76.6 | 55.8 | 70.1 | 52.8 | 68.4 | 23.0 | 33.9 |
| 8 | 5.3 | 5.1 | 60.8 | 77.6 | 55.4 | 72.5 | 58.8 | 75.8 | 53.4 | 70.7 | 49.7 | 64.1 | 46.7 | 62.3 | 24.5 | 36.7 |
| 10 | 5.9 | 5.7 | 59.3 | 76.4 | 53.4 | 70.7 | 57.3 | 74.4 | 51.4 | 68.7 | 47.8 | 62.2 | 44.8 | 60.4 | 25.0 | 37.7 |
| 16 | 7.5 | 7.3 | 56.2 | 73.1 | 48.8 | 65.9 | 54.2 | 71.3 | 46.8 | 64.0 | 43.7 | 58.2 | 40.7 | 56.4 | 25.0 | 38.7 |
| 20 | 8.4 | 8.1 | 54.8 | 71.5 | 46.4 | 63.4 | 52.8 | 69.7 | 44.4 | 61.6 | 41.8 | 56.4 | 38.8 | 54.5 | 25.0 | 38.7 |
| 25 | 9.4 | 9.1 | 53.3 | 70.2 | 44.0 | 61.1 | 51.3 | 68.3 | 42.0 | 59.2 | 39.8 | 54.5 | 36.8 | 52.6 | 24.3 | 35.5 |
| 31.25 | 10.5 | 10.2 | 51.9 | 68.6 | 41.4 | 58.4 | 49.9 | 66.7 | 39.4 | 56.5 | 37.9 | 52.7 | 34.9 | 50.7 | 23.6 | 37.2 |
| 62.5 | 15.0 | 14.6 | 47.4 | 64.2 | 32.4 | 49.6 | 45.4 | 62.3 | 30.4 | 47.7 | 31.9 | 46.6 | 28.9 | 44.7 | 21.5 | 34.6 |
| 100 | 19.1 | 18.6 | 44.3 | 60.8 | 25.2 | 42.1 | 42.3 | 59.0 | 23.2 | 40.3 | 27.8 | 42.5 | 24.8 | 40.5 | 20.1 | 30.3 |
| 155 | 24.1 | 23.4 | 41.4 | 58.4 | 17.4 | 35.0 | 39.4 | 56.4 | 15.4 | 33.0 | 24.0 | 38.9 | 21.0 | 37.0 | 18.8 | 30.8 |
| 200 | 27.6 | 26.8 | 39.8 | 56.0 | 12.2 | 29.2 | 37.8 | 54.2 | 10.2 | 27.4 | 21.8 | 36.6 | 18.8 | 34.6 | 18.0 | 30.0 |
| 250 | 31.1 | 30.1 | 38.3 | 54.3 | 7.3 | 24.2 | 36.3 | 52.5 | 5.3 | 22.3 | 19.8 | 34.6 | 16.8 | 32.6 | 17.3 | 30.5 |
| 300 | 34.3 | 33.1 | 37.1 | 53.1 | 2.9 | 19.9 | 35.1 | 51.2 | 0.9 | 18.1 | 18.3 | 33.1 | 15.3 | 31.2 | 16.8 | 31.1 |
| 350 | 37.2 | 36.0 | 36.1 | 51.8 | -1.1 | 15.8 | 34.1 | 49.9 | -3.1 | 13.9 | 16.9 | 31.9 | 13.9 | 29.9 | 16.3 | 31.7 |
| 400 | 40.1 | 38.8 | 35.3 | 50.8 | -4.8 | 12.0 | 33.3 | 48.8 | -6.8 | 10.0 | 15.8 | 30.6 | 12.8 | 28.6 | 15.9 | 31.5 |
| 500 | 45.3 | 43.6 | 33.8 | 47.9 | -11.4 | 4.3 | 31.8 | 45.8 | -13.4 | 2.2 | 13.8 | 28.7 | 10.8 | 26.7 | 15.2 | 32.0 |
| 550 | | 43.8 | | 48.0 | | 4.1 | | 45.9 | | 2.0 | | 28.6 | | 26.7 | | 31.9 |
| 650 | | 50.2 | | 43.5 | | -6.7 | | 41.5 | | -8.8 | | 25.7 | | 23.5 | | 25.3 |