

Strikes

For (F) XX-R rim devices (center latching)



565

Adjustable surface mounted for use with blade or applied stops.



F570



F490

F570/F490

Adjustable strike.



571/571A

Used on inactive leaf for device on active leaf of pair of doors without removable mullion. 571 keeps 2 7/16" backset. 571A is trimmer and projects less into opening.



579

Semi-surface strike which allows use of XX-R on narrower stile widths as low as 3 1/2". Also used for low projection.

For all mortise lock devices (F) XX-M



1279

To ASA dimensions. Closed strike used on single doors and on fire exit hardware doors with coordinator.



F1280

Open back strike used on pairs of 1 3/4" doors without astragal or coordinator. To basic ASA dimensions and can be used on stock hollow metal doors. Use 1280A for 2 1/4" doors. F-1280 B label (1 1/2 hr.) stainless steel strike available.



1281


Open back strike for 1 3/4" doors. 8" x 1 1/4" ears allow use in mortise lock cutout of stock hollow metal door.



4188

Top strike for (F)XX-C

For (F) XX surface vertical rod and concealed vertical rod devices



4215

Angle bracket for flush transom applications. Does not require elimination of latch retention feature.



3788

Standard top of (F) XX-V.



2126A

(F)XX-V optional bottom strike.
(F)XX-C bottom strike



4155

4155 bottom strike for use with (F)XX-V and (F)XX-C



2130

(F)XX-V standard bottom strike for grouting into concrete or masonry floors. Also used with (F)XX-C

Filler plates



3721/3722/3723

Steel filler plates
3721 Cylindrical lock front filler
3722 ASA Strike filler
— set no. SC for 161 cutout
3723 Mortise lock front filler
3722 ASA Strike filler
— set no. SM for 86 cutout

Surface vertical extension rods



Extension rods are available in 12", 24" and 36" lengths in all finishes. Both ends tapped and all-thread included as connector.

Concealed extension rods



Extension rods are available in 12", 24" and 36". Both ends have pressed-in, threaded inserts.