

MORTISE AND RIM CYLINDER

ED211 Mortise Cylinder Wrench

The BEST® mortise cylinder wrench and test handle is an essential double-purpose tool. It is used primarily to install or remove BEST mortise cylinders without marring the cylinder surface finish. It is also used to align throw pins, and as a testing tool when installing mortise or tubular units. The single end may be used to test the lock operation.

To order specify: ED211 mortise cylinder wrench



ED211

ED212 Mortise Cylinder Cam Assembly Tool

Fast attachment of cams to BEST® mortise cylinders is effected with this important device. It works equally well with adaptation cams, permitting relocking of any masterkeyed mortise lockset through use of BEST replacement cylinders. Approximate length 1 3/4".

To order specify: ED212 mortise tool

ED221 Mortise Cylinder Thread Repair Die

Tool for re-threading 1 5/32" diameter cylinder.

To order specify: ED221 thread repair die 1E cylinder

ED222 Cylinder Cam Testing Tool

Engages throw pins and activates cam≈ for testing.

To order specify: ED222 cylinder cam testing tool



ED212

3ED224 Hole Tap for 1 1/2" Mortise Cylinder

Tap tool is used to re-thread housing threads for 3E mortise cylinders.

To order specify: 3ED224 hole tap for 1 1/2" mortise cylinder

ED225 Hole Tap for 1 5/32" Mortise Cylinder

Tap tool used to re-thread housing threads for 1E mortise cylinder.

To order specify: ED225 hole tap for 1 5/32" mortise cylinder

(Available only to registered BEST® Master Keyed System owners.)