

Milestone  
**HUSKY™ M20**

Access anywhere



Milestone  
Mobile



XProtect®  
Web Client



XProtect®  
Smart Client



# The easiest installation **you've ever** done

Simply connect any camera and the Husky M20 is the quickest route to a complete surveillance solution.

## Product highlights

### Predictable installation every time

Smart Start plug-and-play to connect cameras and configure storage

Smart Start is automatic camera discovery, IP address assignment\*, time synchronization\* and storage allocation

8 or 16 port Integrated Power over Ethernet (PoE) managed switch

PoE+ on all ports, up to 250W total power

*\*For supported cameras*

### Highest performance for the mid market

200 Mbit/s recording rate to handle high-megapixel cameras

Customer replaceable hard disk drives

Alarm I/O: 4 in and 4 out

Latest technology with 6th-generation Intel Skylake processors

Western Digital Purple hard disk drives made for surveillance

Supports up to 32 cameras

### Proven solution that works with any camera

Preloaded with an NVR-optimized version of XProtect Professional

Choose from more than 6,000 cameras from more than 100 manufacturers

**Industry's** best mobile app for free

Connect multiple Milestone Husky NVRs together in master/slave setup

Supports third-party integrations and Milestone add-on products

Includes 3-year hardware warranty

# Milestone HUSKY™ M20

## Front and rear panel



### Front

- A. 2 x HDD bays
- B. 1 x PoE LED
- C. 1 x LAN LED indicator
- D. 1 x HDD LED
- E. 1 x Power LED



### Rear interfaces

- A. 1 x Power switch
- B. 1 x Power input
- C. 1 x DVI / 1 x HDMI up to 1920x1200
- D. 2 x GbE RJ45 support PXE boot from LAN, wake on LAN function
- E. 4 x USB 3.0
- F. 1 x Line-out / MIC-in / Line-in
- G. 1 x eSATA (ASM1153E)
- H. 1 x Alarm I/O (4 in / 4 out, TTL 0/5V)
- I. Network switch: IEEE 802.3at RJ45 x 8/16 with status  
Left-yellow LED to link status on  
Right-green LED to display PoE

## Selecting the right Husky M20

Days of recording	Number of cameras	
	8	16
7	0.4TB	0.6TB
15	0.7TB	1.3TB
30	1.3TB	2.5TB
45	2.5TB	3.8TB
60	3.8TB	--
90	--	--

Calculations for 20% motion-based recording for:  
5MP @ 4fps    1080p @ 10fps    720p @ 22fps    4CIF @ 60fps

For more precise results, please use the Milestone Husky calculator.

## Ordering information

HM20-2T-8P	1x2TB, 8 licenses, i3, 8GB RAM, 8-port PoE
HM20-4T-16	2x2TB, 16 licenses, i3, 8GB RAM
HM20-4T-16P	2x2TB, 16 licenses, i3, 8GB RAM, 16-port PoE
HM20-12T-16P	2x6TB, 16 licenses, i3, 8GB RAM, 16-port PoE
HMCL-4	Add-on licenses, 4-pack for -16 and -16P models
HMCP-XP	1 year Care Plus

Please contact your local Milestone representative to order Milestone Husky M20.

## Specification

General	Detail
Form factor	Standalone or 2U-88mm rack-mount with included rack rails
Type of deployment	Single or multi-unit setup
Dimensions	43(W) x 33(D) x 8.8(H) cm 16.9(W) x 13(D) x 3.5(H) in
Maximum number of cameras	32
Maximum recording rate	200 Mbit/s
Maximum local display	2
Camera licenses included	8 port: 8 / 16 port: 16
Add-on camera licenses	4 pack
Maximum number of users	Unlimited
Dual network interface cards	Yes
CPU	Skylake i3-6100
Passmark	5475
Operating system support	Windows 10 IoT Enterprise
Memory	8GB
Integrated PoE managed switch	Optional, IEEE 802.3at PoE+ (250W total power), port lock, power management, 10/100/1000BASE-T/Tx

Storage system	Detail
Video storage	2TB / 4TB / 12TB SATA 2 customer-serviceable HDD bays
Drive type	Western Digital Purple Drives
VMS/OS storage	128GB mSATA SSD

Video management system	Detail
VMS preloaded	Optimized XProtect Professional
Milestone Care Basic	Included
Milestone Care Plus	Optional
Hardware warranty	Three years included
Smart Start	Yes
Setup wizards	Yes
Supports ONVIF cameras	Yes
Codec support	H.264, MJPEG, MPEG4, MxPEG
Multiple video export formats	Yes
Pan-tilt-zoom (PTZ) support	Yes
Audio support	Yes, two-way
Third-party application support	Yes
Milestone Interconnect support	Yes
Customer Dashboard support	Yes, with Milestone Care Plus

Electrical	Detail
Power input	Non-PoE: 100-240VAC~, 250W PoE: 100-240VAC~, 500W
Maximum power consumption	Non-PoE: 250W PoE: 500W

Environmental	Detail
Operation temperature	0~40°C
Storage temperature	-20°C ~ 70°C
Humidity	10~90% relative humidity (non-condensing)

Other	Detail
Regulatory compliance	CE (class A), WEEE, FCC (class A), RCM, UL, VCCI, Mexico (CoC), South Africa (CoC)
Shipping dimensions	60.7(W) x 23.6 (D) x 47.2 (H) cm 23.8 (W) x 9.3 (D) x 16.8 (H) in
Shipping weight	Approx. 13.5 kg / 30 lbs

Product specifications subject to change without notice.