



### Application

- The 501/421 cable gland provides a seal on the outer cable sheath
- For use on non-armoured elastomer and plastic insulated cables
- Suitable for installation in Zone 1 (21), Zone 2 (22) and Division 2 hazardous areas.

CABLE GLAND SELECTION TABLE

| Size Ref. | Entry Thread Size 'E' |                          | Cable Acceptance Details |                          |                      |      | Fully Compressed Length 'G' | Hexagon Dimensions |                |
|-----------|-----------------------|--------------------------|--------------------------|--------------------------|----------------------|------|-----------------------------|--------------------|----------------|
|           | Metric                | NPT * Standard or Option | Outer Sheath 'B'         |                          |                      |      |                             | Across Flats       | Across Corners |
|           |                       |                          | Standard Seal            |                          | Alternative Seal (S) |      |                             |                    |                |
|           |                       |                          | Min.                     | Max.                     | Min.                 | Max. |                             |                    |                |
| 2K        | M16                   | -                        | 3.2                      | 8.0                      | -                    | -    | 23.5                        | 19.0               | 21.2           |
| Os        | M20 <sup>2</sup>      | ½"                       | 3.2                      | 8.0                      | -                    | -    | 23.8                        | 24.0               | 26.5           |
| O         | M20 <sup>2</sup>      | ½"                       | 6.5                      | 11.9                     | -                    | -    | 23.8                        | 24.0               | 26.5           |
| A         | M20                   | ¾" or ½"                 | 10.0                     | 14.3                     | 9.0                  | 13.4 | 24.8                        | 30.0               | 32.5           |
| B         | M25                   | 1" or ¾"                 | 13.0                     | 20.2                     | 9.5                  | 15.4 | 25.8                        | 36.0               | 39.5           |
| C         | M32                   | 1¼" or 1"                | 19.5                     | 26.5                     | 15.4                 | 21.2 | 28.2                        | 46.0               | 50.5           |
| C2        | M40                   | 1½" or 1¼"               | 25.0                     | 32.5                     | 22.0                 | 28.0 | 29.5                        | 55.0               | 60.6           |
| D         | M50                   | 2" or 1½"                | 31.5                     | 44.4 / 42.3 <sup>1</sup> | 27.5                 | 34.8 | 40.4                        | 65.0               | 70.8           |
| E         | M63                   | 2½" or 2"                | 42.5                     | 56.3 / 54.3 <sup>1</sup> | 39.0                 | 46.5 | 38.2                        | 80.0               | 88.0           |
| F         | M75                   | 3" or 2½"                | 54.5                     | 68.2 / 65.3 <sup>1</sup> | 48.5                 | 58.3 | 40.5                        | 95.0               | 104.0          |
| G         | M80                   | 3½"                      | 67.0                     | 73.0                     | -                    | -    | 41.0                        | 106.4              | 115.0          |
| H         | M90                   | 3½"                      | 67.0                     | 77.6                     | -                    | -    | 41.0                        | 115.0              | 130.0          |
| J         | M100                  | 4"                       | 75.0                     | 91.6                     | -                    | -    | 41.0                        | 127.0              | 142.0          |

'T' — 2K to F size metric entry threads are 1.5mm pitch as standard, 15mm length of thread. For G size glands and above, a 2mm pitch is supplied as standard, 20mm length of thread (1.5mm pitch with 15mm length of thread can be supplied) please specify when ordering.  
All dimensions in millimetres (except \* where dimensions are in inches).

<sup>1</sup> Smaller value is applicable when selecting reduced NPT entry option.

<sup>2</sup> Sizes Os and O are available with an M16 thread size. For O size with M16 thread, the maximum cable outer sheath diameter is 10.9mm

### Technical Data

#### ATEX/IECEx

- Flameproof Exd IIC Gb, Increased Safety Exe IIC Gb and Dust Extb IIIC Db Ex II 2 GD.
- Certificate No's: Baseefa06ATEX0056X and IECEx BAS 06.0013X.
- Suitable for use in Zone 1, Zone 2, Zone 21, Zone 22.
- Construction and Test Standards: IEC/EN 60079-0, IEC/EN 60079-1, IEC/EN 60079-7 and IEC/EN 60079-31.
- Ingress Protection: IP66, IP67 and IP 68 (30 metres for 7 days) to IEC/EN 60529 and NEMA 4X.
- Deluge Protection to DTS01.
- Operating Temperature Range: -60°C to +100°C.
- Assembly Instruction Sheet: AI 307.

#### cCSAus

- Flameproof AExd IIC Gb, Increased Safety AExe IIC Gb and Dust AExtd Zone 21.
- Explosion-proof Class 1 Division 2, Class II Division 2 Groups EFG, Class III.
- Certificate No's: CSA1015065 for Marine Shipboard Cable.
- Construction and Test Standards: UL 60079-0, UL 60079-1, UL 60079-7, ISA 60079-31.
- CSA 22.2 No: 60079-0, CSA 22.2 No: 60079-1, CSA 22.2 No: 60079-7, CSA 22.2 No: 60079-31, UL 2225

### Connection Solutions

www.ehawke.com

### Features

- When used in Increased Safety applications, this cable gland may be used with braided cable where the braid and the outer sheath pass into the enclosure. The braid must then be suitably terminated inside the enclosure.
- Manufactured in Brass (standard), Nickel Plated Brass, 316 Stainless Steel or Aluminium.
- Brass NPT entries are nickel plated as standard.
- Cable glands are marked with ATEX/IECEx and cCSAus certification information as standard.

### Ordering Information

Format for ordering is as follows: Alternative Seal (S), add suffix S to ordering information.

| Cable Gland Type | Size | Thread   | Material | (Optional) |
|------------------|------|----------|----------|------------|
| 501/421          | C    | M32      | Brass    | S          |
| 501/421          | C    | 1 ¼" NPT | Brass    | S          |

