



CC0071597/1 | KP-MOD-48P
Uniprise® Keystone Modular Panel, 48 port

OBSOLETE

This product was discontinued on: May 15, 2016

Replaced By

PP48PNPT

Patch Panel, category 6, KM8 style, 48-port, unloaded, black

Product Classification

Portfolio	Uniprise®
Product Type	Copper patch panel
Regional Availability	North America

Dimensions

Depth	24.13 mm 0.95 in
Height	88.90 mm 3.50 in
Width	482.60 mm 19.00 in

Electrical Specifications

Current Rating	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac @ 60 Hz
Dielectric Withstand Voltage, RMS, contact-to-contact	1000 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Intelligence Type	Passive
Total Ports, quantity	48
Cable Type	U/UTP (unshielded)
Brand	Uniprise®
Color	Black
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	2

Mechanical Specifications

Conductor Gauge, solid	22 AWG 24 AWG
Conductor Gauge, stranded	22 AWG 24 AWG
Conductor Type	Solid Stranded
Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
Plug Insertion Life, minimum	750 times
Plug Insertion Life, test plug	IEC 60603-7 compliant plug
Plug Retention Force, minimum	30 lb/ft
Rear Termination Type	IDC
Wiring	T568A T568B

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system