THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



CT-2940/ST • CT-2940/STINT • CT-2940/STUK • CT-2940/STAUS • CT-2940/TO

**CRIMP TOOL** 

This tool meets requirements of Safety for Hand Heldheld, Motor-Operated Electric Tools specification UL 60745-1 and CSA C22.2 No 60745-1. Tool is listed under CSA file number 268531.

## NOTES, UNLESS OTHERWISE SPECIFIED:

The CT-2940/ST, CT-2940/STINT, CT-2940/STUK, CT-2940/STAUS and CT-2940/TO Battery Operated Crimping Tools are designed to crimp:

• Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to <a href="https://www.panduit.com">www.panduit.com</a> for more information.

## The CT-2940/ST, CT-2940/STINT, CT-2940/STUK and CT-2940/STAUS Tools include:

Qty.	Description / Item							
1	Battery Operated Hydraulic Crimp Tool							
2	Rechargeable Battery (Makita Lithium-Ion 18VDC, 3Ah)							
	Makita Battery Charger – Regional (reference images below for regional plug type)							
	/ST	/STINT	/STUK	/STAUS				
1	Plug Type A (North America)	Plug Type C (International)	Plug Type G (UK)	Plug Type I (Australia)				
1	Plastic Tool Case with Die Storage							
1	Tool Carrying Strap							
1	Set of Panduit "CD-940-DAPT" Die Adapters							
1	Assist Handle (Not Shown)							

## The CT-2940/TO Tool includes:

C	Qty.	Description / Item				
	1	Battery Operated Hydraulic Crimp Tool				
	1	Set of Panduit "CD-940-DAPT" Die Adapters				

## **Technical Information:**

•					
	Tool Weight (including battery)	15.7 lbs. (7.1 kg)			
	Dimensions (including battery)	16.22" L x 12.56" H x 2.91" W [412 L x 319 H x 74 W] mm			
	Crimping Force	15 tons (135 kN)			

Tools are to be used with Panduit crimp dies, and are sold separately. Go to <a href="https://www.panduit.com">www.panduit.com</a> for more information.

A copy of the operation manual and accessory information can be found at: <a href="https://www.panduit.com">www.panduit.com</a>.

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

							CT-2940/ST, CT-2940/STINT, CT-2940/STUK, CT-2940/STAUS and CT-2940/TO CUSTOMER DRAWING		
							1TEM REVISION NAME: 00084SLD_DC/00	IIT	
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± (.xxx) ± (.xx) ± ANGLES ±		
00	7-25-16	BKA	ACC	JADE	DRAWING RELEASED	010819	THIRD ANGLE PROJECTION DRAWING NUMBER: 00084SLD_DC		
REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	I DI DI I 7 O4 40 I DIDII I NONE I CIIT 4 CE 4 I	ze 3	