


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NO.	DIMENSIONS						WEIGHT
	A (REF)	B (REF)	C	D	E (REF)	F	lbs / 50pcs (kg) / 50pcs
BR-1.5-PAF	1.50 [38]	3.15 [80]	0.32 [8] MINIMUM	0.209 [5.3] 0.201 [5.1]	2.00 [51]	1.15 [29] 1.35 [34]	5.6 (2.5)
BR-2.0-PAF	2.00 [51]	3.63 [92]	0.32 [8] MINIMUM	0.209 [5.3] 0.201 [5.1]	2.00 [51]	1.15 [29] 1.35 [34]	6.4 (2.9)



- NOTES:
1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE.
 2. PART TO BE SECURED USING POWDER ACTUATED TOOL.

DIMENSIONS IN BRACKETS ARE METRIC [mm]	
CAD FILENAME/LAYERS G03668DV_DC_GB3668DV/OOA	
PANDUIT CORP. TINLEY PARK, ILLINOIS	
BR-_-PAF BRIDLE RING W/POWDER ACTUATED FASTENER	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ±0.05 (1.3) (.XXX) ±0.010 (0.25) (.XX) ±0.02 (0.5) ANGLES ±5°	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.
DRAWN BY ARHA DATE 09-15-09 CHK'D KEN	MAT'L: LOW CARBON STEEL BRIGHT ZINC ELECTROPLATE
SCALE NONE	DWG A
DRAWING NO. GB3668DV	SIZE

OOA	09/15/09	ARHA	gmk	INITIAL RELEASE	GB3668DV	OOA	KEN		
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	