PANDUIT P/N	WEIGHT
P36D08M	9.4kg



REAR VIEW



TOP VIEW

NOTES:

1. IDENTIFICATION:

UNIT TYPE:	MONITORED INPUT
ORIENTATION:	VERTICAL, 0U, FULL
OUTLET QTY&TYPE:	(30) C13, (6) C19
BREAKER QTY&TYPE:	(3) 20AMP, DOUBLE-POLE
INPUT VOLTAGE:	200-240VAC, DELTA
INPUT CURRENT:	30A (24A DERATED)
INPUT PHASE:	THREE-PHASE, DELTA
RATED POWER:	8.6 kVA
INPUT PLUG:	NEMA L15-30P
INPUT CORD LENGTH:	3m [10']

2. ACCESSORIES:
   POCKET GUIDE
3. RoHS COMPLIANT
4. VISIT PANDUIT'S ON-LINE CATALOG AT WWW.PANDUIT.COM FOR ADDITIONAL PRODUCT INFORMATION CONTAINED IN THE SPECIFICATION SHEET AS WELL AS A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
5. MAXIMUM ALLOWABLE INPUT POWER = 8.6kW
6. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES



FRONT VIEW



SIDE VIEW

PLUG
30 AMP, 250V x 3~ DELTA
TWIST LOCK
NEMA L15-30P

SIX(6)
RECEPTACLES
16 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19



THIRTY (30)
RECEPTACLES
10 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
01A	07/17/2017	WSJ	MIM	EDM	INITIAL RELEASE	P36D08M

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY

SIGN

DATE

PRINT

TITLE
INTELLIGENT SERIES PDU
P36D08M
CUSTOMER DRAWING

ITEM REVISION NAME

DATASHEET FILE NAME:

UNLESS OTHERWISE SPECIFIED
DIMENSIONAL TOLERANCE ARE: mm [IN]

THIRD ANGLE PROJECTION

Tolerance(mm)	
0<L<200	±0.5
200<L<500	±1.5
500<L<1000	±2.5
1000<L<2000	±4.0

MATERIAL/COLOR:
N/A

DRAWING NUMBER:
P36D08M_DC

DRAWN BY	DATE	CHK	SCALE	SCALE
WSJ	07/17/2017	SEAN	NONE	B

SHT 1 OF 1