

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ARALDITE® 2015 RESIN(E)/HARZ

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

#### 1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA  
Address : Everslaan 45  
3078 Everberg  
Belgium  
Telephone : +41 61 299 20 41  
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

#### 1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
+86 532 83889090  
India: + 91 22 42 87 5333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Hazard pictograms :



Signal word : Danger

Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H318	Causes serious eye damage.
		H411	Toxic to aquatic life with long lasting effects.

Precautionary statements	:	<b>Prevention:</b>	
		P261	Avoid breathing mist or vapours.
		P264	Wash skin thoroughly after handling.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ eye protection/ face protection.
		<b>Response:</b>	
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.	
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

1,4-bis(2,3-epoxypropoxy)butane

bisphenol A - epoxy resins, number average MW >700 - <1100

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 30 - < 50

## ARALDITE® 2015 RESIN(E)/HARZ

Version 1.1      Revision Date: 13.06.2018      SDS Number: 400001009041      Date of last issue: 16.02.2017  
Date of first issue: 16.02.2017

	01-2119456619-26	Aquatic Chronic 2; H411	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5 500-006-8 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 3 - < 10
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
2-[[3-Hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate	60506-81-2 262-270-8 01-2119980666-22	Eye Irrit. 2; H319	>= 1 - < 10
Hydroquinone	123-31-9 204-617-8 604-005-00-4 -	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.025 - < 0.1

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorohydrin

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Treat symptomatically.  
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No data is available on the product itself.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Personal precautions : Use personal protective equipment.  
Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,  
For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust.			

## ARALDITE® 2015 RESIN(E)/HARZ

Version 1.1      Revision Date: 13.06.2018      SDS Number: 400001009041      Date of last issue: 16.02.2017  
Date of first issue: 16.02.2017

	This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
mica	12001-26-2	TWA (Inhalable)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable)	0.8 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Hydroquinone	123-31-9	TWA	0.5 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			

Not applicable

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12.25 mg/m3
	Workers	Dermal	Systemic effects, Long-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12.25 mg/m3
	Consumers	Dermal	Systemic effects, Short-term exposure	3.571 mg/kg bw/day



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

**ARALDITE® 2015 RESIN(E)/HARZ**

Version 1.1      Revision Date: 13.06.2018      SDS Number: 400001009041      Date of last issue: 16.02.2017  
 Date of first issue: 16.02.2017

	Consumers	Oral	Systemic effects, Short-term exposure	0.75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3.571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0.75 mg/kg bw/day
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	Workers	Dermal	Acute local effects	0.0083 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term systemic effects	104.15 mg/kg
	Workers	Inhalation	Long-term systemic effects	29.39 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	62.5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8.7 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	6.25 mg/kg

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l
Remarks:	Assessment Factors	
	Marine water	0.0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.018 mg/l
	Assessment Factors	
	Fresh water sediment	0.996 mg/kg
	Equilibrium method	
	Marine sediment	0.0996 mg/kg
	Equilibrium method	
	Soil	0.196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
bisphenol F-epoxy resin	Fresh water	0.003 mg/l



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

**ARALDITE® 2015 RESIN(E)/HARZ**Version  
1.1Revision Date:  
13.06.2018SDS Number:  
400001009041Date of last issue: 16.02.2017  
Date of first issue: 16.02.2017

	Assessment Factors	
	Marine water	0.0003 mg/l
	Assessment Factors	
	Intermittent use/release	0.0254 mg/l
	Assessment Factors	
	Fresh water sediment	0.294 mg/kg
	Equilibrium method	
	Marine sediment	0.0294 mg/kg
	Equilibrium method	
	Soil	0.237 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l
	Assessment Factors	
	Marine water	0.0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.018 mg/l
	Assessment Factors	
	Fresh water sediment	0.996 mg/kg
	Equilibrium method	
	Marine sediment	0.0996 mg/kg
	Equilibrium method	
	Soil	0.196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Fresh water	0.003 mg/l
	Assessment Factors	
	Marine water	0.0003 mg/l
	Assessment Factors	

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

	Intermittent use/release	0.0254 mg/l
	Assessment Factors	
	Fresh water sediment	0.294 mg/kg
	Equilibrium method	
	Marine sediment	0.0294 mg/kg
	Equilibrium method	
	Soil	0.237 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
Siloxanes and Silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg
	Assessment Factors	
	Soil	23 mg/kg
	Assessment Factors	

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)  
Break through time : > 8 h

Material : Nitrile rubber  
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Filter type : Combined particulates and organic vapour type (A-P)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: paste
Colour	: beige
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: ca. 6 - 7 (25 °C) Concentration: 500 g/l
Freezing point	: No data is available on the product itself.
Melting point	: No data is available on the product itself.
Boiling point	: > 200 °C
Flash point	: > 150 °C Method: Pensky-Martens closed cup, closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0.002 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: 1.4 g/cm <sup>3</sup> (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity  
Viscosity, dynamic : thixotropic

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Carbon oxides  
Burning produces noxious and toxic fumes.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate : > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Acute dermal toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

### Skin corrosion/irritation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild skin irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method: OECD Test Guideline 404

Result: Skin irritation

Hydroquinone:

Species: Rabbit

Assessment: No skin irritation

Result: No skin irritation

### Serious eye damage/eye irritation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Method: OECD Test Guideline 405

Result: Risk of serious damage to eyes.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

2-[[3-Hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

Result: Eye irritation

Hydroquinone:

Assessment: Risk of serious damage to eyes.

Result: Risk of serious damage to eyes.

### Respiratory or skin sensitisation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

1,4-bis(2,3-epoxypropoxy)butane:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Hydroquinone:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

Assessment: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

### Germ cell mutagenicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive

: Concentration: 0 - 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive

: Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: positive

: Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive

1,4-bis(2,3-epoxypropoxy)butane:

Genotoxicity in vitro : Concentration: 10 - 5000 ug/plate  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: positive  
Remarks: Not classified due to data which are conclusive although insufficient for classification.

: Concentration: 1 - 100 µg/L  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: positive  
Remarks: Not classified due to data which are conclusive although insufficient for classification.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: Positive results were obtained in some in vitro tests.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

: Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative

### Hydroquinone:

#### Genotoxicity in vitro

: Metabolic activation: with and without metabolic activation  
Result: positive

: Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

: Test Type: Chromosome aberration test in vitro  
Test system: Human lymphocytes  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative  
GLP: yes

: Test Type: Chromosome aberration test in vitro  
Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive

### Components:

#### 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

##### Genotoxicity in vivo

: Cell type: Germ  
Application Route: Oral  
Method: OECD Test Guideline 478  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 0 - 5000 mg/kg  
Method: OPPTS 870.5395  
Result: negative

#### Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

##### Genotoxicity in vivo

: Cell type: Somatic  
Application Route: Oral  
Exposure time: 48 h  
Dose: 2000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Method: OECD Test Guideline 474  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 2000 mg/kg  
Method: OECD Test Guideline 486  
Result: negative

1,4-bis(2,3-epoxypropoxy)butane:

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Test species: Mouse  
Cell type: Somatic  
Application Route: Oral  
Exposure time: 4 d  
Dose: 187.5 - 750 mg/kg  
Method: OECD Test Guideline 474  
Result: negative

Test Type: unscheduled DNA synthesis assay  
Test species: Rat  
Cell type: Liver cells  
Application Route: Oral  
Method: OECD Test Guideline 486  
Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vivo : Cell type: Germ  
Application Route: Oral  
Method: OECD Test Guideline 478  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 0 - 5000 mg/kg  
Method: OPPTS 870.5395  
Result: negative

Hydroquinone:

Genotoxicity in vivo : Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 483  
Result: positive

Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: positive

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Application Route: Oral  
Exposure time: 10 Weeks  
Method: OECD Test Guideline 478  
Result: negative

### **Components:**

1,4-bis(2,3-epoxypropoxy)butane:

Germ cell mutagenicity-  
Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Hydroquinone:

Germ cell mutagenicity-  
Assessment : In vitro tests showed mutagenic effects

Germ cell mutagenicity-  
Assessment : No data available

### **Carcinogenicity**

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week

Method: OECD Test Guideline 453

Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Dose: 15 mg/kg  
Frequency of Treatment: 7 daily  
Method: OECD Test Guideline 453  
Result: negative

Hydroquinone:  
Species: Rat  
Application Route: Oral  
Exposure time: 103 weeks  
Frequency of Treatment: 5 daily  
Method: OECD Test Guideline 453  
Result: positive

Species: Mouse  
Application Route: Oral  
Exposure time: 103 weeks  
Frequency of Treatment: 5 daily  
Method: OECD Test Guideline 453  
Result: positive

### **Components:**

Hydroquinone:  
Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **Reproductive toxicity**

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:  
Effects on fertility : Test Type: Two-generation study  
Species: Rat, male and female  
Application Route: Oral  
Dose: >750 milligram per kilogram  
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight  
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight  
Symptoms: No adverse effects  
Method: OECD Test Guideline 416  
Result: No effects on fertility and early embryonic development were detected.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:  
Species: Rat, male and female  
Application Route: Oral  
Method: OECD Test Guideline 416  
Result: No effects on fertility and early embryonic development were detected.

bisphenol A - epoxy resins, number average MW >700 - <1100:  
Species: Rat, male and female  
Application Route: Oral  
General Toxicity - Parent: No-observed-effect level: 750

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

mg/kg body weight  
General Toxicity F1: No-observed-effect level: 750 mg/kg  
body weight  
Method: OECD Test Guideline 416  
Result: No effects on fertility and early embryonic  
development were detected.

Hydroquinone:

Species: Rat  
Application Route: Oral  
Method: EPA OTS 798.4100

### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Method: Other guidelines  
Result: No teratogenic effects

Species: Rabbit, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
60 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rat, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Result: No teratogenic effects

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Method: Other guidelines  
Result: No teratogenic effects

Species: Rabbit, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

60 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rat, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Hydroquinone:

Species: Rat  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
100 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rabbit  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
25 mg/kg body weight  
Method: EPA OTS 798.4900  
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Repeated dose toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

NOAEL: 100 mg/kg  
Application Route: Skin contact  
Exposure time: 13 WeeksNumber of exposures: 3 d  
Method: Subchronic toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:  
Species: Rat, male and female  
NOAEL: 250 mg/kg  
Application Route: Ingestion  
Exposure time: 13 WeeksNumber of exposures: 7 d  
Method: Subchronic toxicity

1,4-bis(2,3-epoxypropoxy)butane:  
Species: Rat, male and female  
NOAEL: 200 mg/kg  
Application Route: Ingestion  
Exposure time: 28 dNumber of exposures: 7 d  
Method: Subacute toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:  
Species: Rat, male and female  
NOAEL: 50 mg/kg  
Application Route: Ingestion  
Exposure time: 14 WeeksNumber of exposures: 7 d  
Method: Subchronic toxicity

Species: Rat, male and female  
NOEL: 10 mg/kg  
Application Route: Skin contact  
Exposure time: 13 WeeksNumber of exposures: 5 d  
Method: Subchronic toxicity

Hydroquinone:  
Species: Mouse  
LOAEL: 100  
Application Route: Ingestion  
Exposure time: 13 WeeksNumber of exposures: 5 d  
Method: Subchronic toxicity

Species: Rat  
LOAEL: 100  
Application Route: Ingestion  
Exposure time: 13 WeeksNumber of exposures: 5 d  
Method: Subchronic toxicity

Species: Rat  
NOAEL: 109.6  
Application Route: Skin contact  
Exposure time: 13 WeeksNumber of exposures: 5 d  
Method: Subchronic toxicity

Repeated dose toxicity - : No data available  
Assessment



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

### Aspiration toxicity

No data available

### Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

### Toxicology, Metabolism, Distribution

No data available

### Neurological effects

No data available

### Further information

Ingestion: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.7 mg/l  
aquatic invertebrates  
Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Test substance: Fresh water  
Method: OECD Test Guideline 211

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to fish : LC50 (Fish): 2.54 mg/l  
Exposure time: 96 h  
Method: Calculation method

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.55 mg/l  
Exposure time: 48 h  
Method: Calculation method

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 1.8 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Test substance: Fresh water  
Method: OECD Test Guideline 211  
Remarks: Information given is based on data obtained from similar substances.

1,4-bis(2,3-epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l  
Exposure time: 24 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 202

Toxicity to algae : EL50 : > 160 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 209

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: no

Hydroquinone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.638 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.134 mg/l  
Exposure time: 48 h  
Test Type: semi-static test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 0.33 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : IC50 (activated sludge): 71 mg/l  
Exposure time: 2 h  
GLP:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.0057 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

### 12.2 Persistence and degradability

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)  
pH: 4  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)  
pH: 9  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)  
pH: 7  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Biodegradability : Inoculum: activated sludge  
Concentration: 3 mg/l  
Result: Not biodegradable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Biodegradation: ca. 0 %  
Exposure time: 28 d  
Method: Directive 67/548/EEC Annex V, C.4.E.

1,4-bis(2,3-epoxypropoxy)butane:

Biodegradability : Inoculum: activated sludge  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 43 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic  
Inoculum: Sewage (STP effluent)  
Concentration: 20 mg/l  
Result: Not biodegradable  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)  
pH: 4  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)  
pH: 9  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)  
pH: 7  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Hydroquinone:

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Concentration: 100 mg/l  
Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 14 d  
Method: OECD Test Guideline 301C

### 12.3 Bioaccumulative potential

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31  
Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (25 °C)

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

Partition coefficient: n-octanol/water : log Pow: 0.59

bisphenol A - epoxy resins, number average MW >700 - <1100:  
Distribution among : Koc: 445  
environmental compartments

Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..
------------	---

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

## SECTION 14: Transport information

**IATA**

**14.1 UN number** : UN 3082

**14.2 UN proper shipping name** : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

**14.3 Transport hazard class(es)** : 9

**14.4 Packing group** : III

Labels : Miscellaneous

Packing instruction (cargo aircraft) : 964

Packing instruction (passenger aircraft) : 964

**IATA (Passenger)**

Environmentally hazardous : yes

**IATA (Cargo)**

Environmentally hazardous : yes

**IMDG**

**14.1 UN number** : UN 3082



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

**14.2 UN proper shipping name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

**14.3 Transport hazard class(es)** : 9

**14.4 Packing group** : III

Labels : 9

EmS Code : F-A, S-F

**14.5 Environmental hazards**  
Marine pollutant : yes

### ADR

**14.1 UN number** : UN 3082

**14.2 UN proper shipping name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

**14.3 Transport hazard class(es)** : 9

**14.4 Packing group** : III

Labels : 9

**14.5 Environmental hazards**  
Environmentally hazardous : yes

### RID

**14.1 UN number** : UN 3082

**14.2 UN proper shipping name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

**14.3 Transport hazard class(es)** : 9

**14.4 Packing group** : III

Labels : 9

**14.5 Environmental hazards**  
Environmentally hazardous : yes

### Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

REACH - List of substances subject to authorisation - : Not applicable  
Future sunset date

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### The components of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the Canadian NDSL.

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOEC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

## 15.2 Chemical safety assessment

### SECTION 16: Other information

#### Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H341	: Suspected of causing genetic defects.
H351	: Suspected of causing cancer.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Muta.	: Germ cell mutagenicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® 2015 RESIN(E)/HARZ

Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2017
1.1	13.06.2018	400001009041	Date of first issue: 16.02.2017

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.