

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name BOSTIK 9252 PRIMER
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers, Sealers, and Undercoaters.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration toxicity	Category 1 - (H304)
Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Toluene, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, Xylenes (o-, m-, p- isomers), Ethylbenzene

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02



Signal Word
DANGER

Hazard statements

H412 - Harmful to aquatic life with long lasting effects
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H304 - May be fatal if swallowed and enters airways
H373 - May cause damage to organs through prolonged or repeated exposure
H361d - Suspected of damaging the unborn child
H225 - Highly flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Additional information

This product requires child resistant fastenings if supplied to the general public
This product requires child resistant fastenings when supplied to the general public unless the product is placed on the market in the form of aerosols or in a container with a sealed spray attachment

2.3. Other Hazards

General Hazards

In use may form flammable/explosive vapour-air mixture.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Ethyl acetate	205-500-4	141-78-6	>25 - <40	Eye Irrit. 2 (H319) STOT SE 3 (H336)		01-2119475103-46 -XXXX

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

				Flam. Liq. 2 (H225) (EUH066)		
Toluene	203-625-9	108-88-3	15 - 25	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)		01-2119471310-51 -XXXX
Methyl ethyl ketone	201-159-0	78-93-3	5 - <10	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119457290-43 -XXXX
Rosin	232-475-7	8050-09-7	5 - <10	Skin Sens. 1 (H317)		01-2119480418-32 -XXXX
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) (EUH066)		01-2119473851-33 -XXXX
Xylenes (o-, m-, p- isomers)	215-535-7	1330-20-7	1 - <5	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	::	01-2119488216-32 -XXXX
Ethylbenzene	202-849-4	100-41-4	0.1 - <1	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)		01-2119489370-35 -XXXX
Ethanolamine	205-483-3	141-43-5	0.1 - <1	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Corr. 1B (H314)	STOT SE 3 :: C>=5%	01-2119486455-28 -XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air.
Skin Contact	Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Safety Data Sheet

BOSTIK 9252 PRIMER
Supercedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
Self-Protection of the First Aider	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Irritating to eyes. Irritating to skin. May cause allergic skin reaction. Drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Observe risk of aspiration if vomiting occurs. Aspiration into lungs can produce severe lung damage.

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use CO₂, dry chemical, or foam. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3. Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.

Water spray may reduce vapour; but may not prevent ignition in closed spaces.

For emergency responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

6.3. Methods and material for containment and cleaning up

Methods for Containment Dyke far ahead of spill; use dry sand to contain the flow of material.

Methods for cleaning up Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Use clean non-sparking tools to collect absorbed material.

6.4. Reference to other sections

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

Reference to other sections See Section 12: ECOLOGICAL INFORMATION
Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ ventilating/ lighting/ equipment.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep only in the original container/package in a cool well-ventilated place. Keep from freezing.

7.3. Specific end use(s)

Other Information

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Ethyl acetate 141-78-6	-	TWA: 200 ppm STEL: 400 ppm	STEL: 400 ppm TWA: 200 ppm
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100ppm STEL: 384mg/m ³ S*	TWA: 50 ppm TWA: 192 mg/m ³ STEL: 384 mg/m ³ STEL: 100 ppm Skin nota.	STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 191 mg/m ³ Skin
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Skin nota.	STEL: 300 ppm STEL: 899 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³ Skin
Rosin 8050-09-7	-	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³ Sensitiser	TWA: 0.05 mg/m ³ fume
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ S*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Skin nota.	STEL: 100 ppm STEL: 441 mg/m ³ TWA: 50 ppm TWA: 220 mg/m ³ Skin
Magnesium oxide (MgO) 1309-48-4	-	TWA: 4 mg/m ³ TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³ STEL: 12 mg/m ³ STEL: 30 mg/m ³	STEL: 30 mg/m ³ inhalable dust STEL: 12 mg/m ³ fume and respirable dust TWA: 10 mg/m ³ inhalable dust TWA: 4 mg/m ³ fume and respirable dust
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ S*	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ Skin nota.	STEL: 125 ppm STEL: 552 mg/m ³ TWA: 100 ppm TWA: 441 mg/m ³ Skin
Talc 14807-96-6	-	TWA: 10 mg/m ³ TWA: 0.8 mg/m ³ STEL: 30 mg/m ³ STEL: 2.4 mg/m ³	STEL: 3 mg/m ³ respirable dust TWA: 1 mg/m ³ respirable dust

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

Ethanolamine 141-43-5	TWA: 1 ppm TWA: 2.5 mg/m ³ STEL: 3ppm STEL: 7.6mg/m ³ S*	TWA: 1 ppm TWA: 2.5 mg/m ³ STEL: 3 ppm STEL: 7.6 mg/m ³ Skin nota.	STEL: 3 ppm STEL: 7.6 mg/m ³ TWA: 1 ppm TWA: 2.5 mg/m ³ Skin
--------------------------	--	--	--

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield.
Hand Protection Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Skin and Body Protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
Respiratory Protection In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection.
Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid
Appearance Liquid
Colour Yellow Brown
Odour Aromatic
Odour Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	77 °C / 170.6 °F	
Flash Point	-9 °C / 15.8 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper flammability or explosive limits	No information available	
Lower flammability or explosive limits	No information available	
Vapour Pressure	No information available	
Vapour Density	No information available	
Relative Density	1.0	
Water Solubility	No information available	
Solubility in Other Solvents	No information available	
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Explosive Properties	No information available	
Oxidising Properties	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	approx 600 mPa s	

Safety Data Sheet

BOSTIK 9252 PRIMER
Supercedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

9.2. Other information

Softening Point	No information available
Molecular Weight	No information available
Solvent content (%)	No information available
Solid content (%)	approx 30
Density	No data available
Bulk Density	No data available
VOC content (%)	

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended storage conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from heat, sparks and flames.

10.5. Incompatible materials

Strong acids and bases.

10.6. Hazardous decomposition products

Carbon oxides.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

Inhalation	No data available.
Eye contact	Severely irritating to eyes.
Skin Contact	Irritating to skin.
Ingestion	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.
Sensitisation	May cause sensitisation by skin contact.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation Not applicable.

Serious eye damage/eye irritation Not applicable.

Safety Data Sheet

BOSTIK 9252 PRIMER
 Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
 Revision Number 1.02

Sensitisation	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Carcinogenicity	Not applicable.
Reproductive Toxicity	Contains a known or suspected reproductive toxin.
STOT - Single Exposure	No information available.
STOT - Repeated Exposure	Causes damage to organs through prolonged or repeated exposure.
Target Organ Effects	Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin, Thyroid.
Aspiration hazard	Risk of serious damage to the lungs (by aspiration). May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

ATEmix (dermal)	24,331.00 mg/kg
ATEmix (inhalation-dust/mist)	88.00 mg/l

Component Information

Toxicity Data Data obtained on the component(s) include

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit)	LC0 29.3 mg/l air
Toluene 108-88-3	= 5580 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	> 20 mg/L (Rat) 4 h
Methyl ethyl ketone 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Rosin 8050-09-7	>2800 mg/Kg (rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Ethyl acetate 141-78-6	EC50 48 h = 3300 mg/L (Desmodesmus subspicatus)	LC50 96 h 220 - 250 mg/L (Pimephales promelas flow-through) LC50 96 h 352 - 500 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h = 484 mg/L (Oncorhynchus mykiss flow-through)	EC50 48 h = 560 mg/L (Daphnia magna Static)	
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8	EC50 48 h = 11.5 mg/L (Daphnia magna) EC50 48 h 5.46 - 9.83 mg/L (Daphnia	

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

		mg/L (Oncorhynchus mykiss semi-static)	magna Static)	
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50 96 h 3130 - 3320 mg/L (Pimephales promelas flow-through)	EC50 48 h > 308 mg/L (Daphnia magna)	
Rosin 8050-09-7	EC50 72 h = 400 mg/L (Desmodesmus subspicatus)	LC50 (96h) >10mg/L Fish (Danio rerio)	EC50 48 h >100 mg/L (Daphnia magna)	
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 48 h = 3.4 mg/L (water flea)	
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna)	
Ethanolamine 141-43-5	EC50 72 h = 15 mg/L (Desmodesmus subspicatus)	LC50 96 h 300 - 1000 mg/L (Lepomis macrochirus static) LC50 96 h = 227 mg/L (Pimephales promelas flow-through) LC50 96 h = 3684 mg/L (Brachydanio rerio static) LC50 96 h > 200 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h 114 - 196 mg/L (Oncorhynchus mykiss static)	EC50 48 h = 65 mg/L (Daphnia magna)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Dispose of wastes in an approved waste disposal facility.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other Information Waste codes should be assigned by the user based on the application for which the

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

product was used.

Section 14: TRANSPORT INFORMATION

Land transport (ADR/RID)

14.1 UN Number	UN1263
14.2 Proper Shipping Name	Paint related material
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing Group	II
Description	UN1263, Paint related material, 3, II, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	163, 640D, 650, 367
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN Number	UN1263
14.2 Proper Shipping Name	Paint related material
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1263, Paint related material, 3, II, (-9°C c.c.)
14.5 Marine Pollutant	Np
14.6 Special Provisions	163, 367
Limited Quantity (LQ)	5 L
EmS-No	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number	UN1263
14.2 Proper Shipping Name	Paint related material
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1263, Paint related material, 3, II
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3, A72, A192
Limited Quantity (LQ)	1 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No.

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No	Restrictions on use
Toluene	108-88-3	48.

48 . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
or
P5b - FLAMMABLE LIQUIDS
or
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

None

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H361d - Suspected of damaging the unborn child
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H304 - May be fatal if swallowed and enters airways
H225 - Highly flammable liquid and vapour
H335 - May cause respiratory irritation
H319 - Causes serious eye irritation
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H226 - Flammable liquid and vapour
H412 - Harmful to aquatic life with long lasting effects
H317 - May cause an allergic skin reaction
H411 - Toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls and personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation
PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

Safety Data Sheet

BOSTIK 9252 PRIMER
Supersedes Date: 13-Dec-2017

Revision Date 18-Jul-2018
Revision Number 1.02

STOT (RE): Specific target organ toxicity - Repeated exposure
STOT (SE): Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 18-Jul-2018

Indication of changes

Revision Note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet