

# LANscape® Fibre Housing, LC Duplex UPC

12 Fibres, 1U, Singlemode OS2, front panel loaded with adapters (Breakout version), black

CORNING

The LANscape® housing family was designed for various applications in 19-in racks and main distribution frames. The fixed or sliding housings can be equipped with industry common adapter types in different fibre categories and are suitable for direct field termination, fusion splicing with pigtails as well as preterminated solutions. The four back openings accommodate cable glands. Additional brackets for cable strain relief for FTDD/FTTO applications or U-Clips for Plug & Play™ and EDGE™ trunks can be mounted at the backside.

The space-optimized interior makes it easy to work with ongoing moves, adds and changes (MACs), thus reducing the risk of network disruptions.

## Features and Benefits

### Easy to remove top cover

No tools needed

### Housing made of aluminium

Lightweight, but robust

### Quick-mount feature

Allows single-person mounting of housing

### Accomodate different termination methods

Pigtail splicing, field connectorisation, preterminated cables, Plug & Play™ or EDGE™ trunks can be installed in the same housing

### Low installation depth

Mountable in shallow cabinets or racks

### Multiple labelling options

Port numbering above and below adapter modules or customised labels

### LC Duplex adapter modules with self-closing shutters

Additional protection at no extra cost



## Specifications

General Specifications	
Mounting type	Rack 19"
Access type	Front, top, rear
Lockable	Yes
Fibre category	Single-mode (OS2)
Application	Field connectorization, pre-terminated cables

# LANscape® Fibre Housing, LC Duplex UPC

12 Fibres, 1U, Singlemode OS2, front panel loaded with adapters (Breakout version), black

CORNING

## Temperature Range

Operation	-10 °C to 60 °C
Storage	-10 °C to 60 °C
Installation and assembly	-10 °C to 60 °C

## Design - Hardware

Housing material	Aluminum
Housing colour	Black
Height unit	1U
Fibre count	12
Cable entry type	Prepunched circular for cable glands (2 x M20 and 2 x M25 on the rear)
Number of adapters	6
Number of pigtails	0
Connector type	LC duplex UPC
Number of splice trays	0
Number of splice protectors	0
Total splice capacity	0
Maximum cable number in basic unit with accessories	4
Additional cable number reachable with accessories	4

## Mechanical Characteristics

Dimensions (HxWxD)	44 mm x 483 mm x 233 mm
--------------------	-------------------------

## Design Adapter

Adapter type	LC duplex UPC shuttered
Adapter housing colour	Blue
Shuttered adapter	Yes

# LANscape® Fibre Housing, LC Duplex UPC

12 Fibres, 1U, Singlemode OS2, front panel loaded with adapters (Breakout version), black



## Ordering Information

Part Number	LAN1-12AE-ADPT-B
Product Description	LANscape® Fibre Housing, front panel loaded with LC Duplex UPC shuttered adapters (Breakout version), 12 Fibres, 1U, Singlemode OS2, black

## Shipping Information

Units Per Delivery	1/1
Package Contents	LANscape Fibre Housing with adapters, 1 x M20 cable gland and all accessories needed for the installation



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified.  
© 2018 Corning Optical Communications. All rights reserved.