THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



CT-2931/STCV • CT-2931/STCVINT • CT-2931/STCVUK • CT-2931/STCVAUS • CT-2931/CVTO

> **CRIMP TOOL WITH DUAL-LAYER PVC HEAD COVER**

This tool meets requirements of Safety for Hand Heldheld, Motor-Operated Electric Tools specification UL 60745-1 and CSA C22.2 No 60745-1. Tool is listed under CSA file number 268531.

NOTES, UNLESS OTHERWISE SPECIFIED:

The CT-2931/STCV, CT-2931/STCVINT, CT-2931/STCVUK, CT-2931/STCVAUS & CT-2931/CVTO Battery Operated Crimping Tools with Dual-Layer PVC Head Cover are designed to crimp:

• Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to www.panduit.com for more information.

CT-2931/STCV, CT-2931/STCVINT, CT-2931/STCVUK and CT-2931/STCVAUS Tools include:

| Qty. | Description / Item | | | | | | | |
|------|--|--|--|---|--|--|--|--|
| 1 | Battery Operated Hydraulic Crimp Tool with Dual-Layer PVC Head Cover | | | | | | | |
| 2 | Rechargeable Battery (Makita Lithium-Ion 18VDC, 3Ah) | | | | | | | |
| 1 | Makita Battery Charge /STCV Plug Type A (North America) | | | or regional plug type) /STCVAUS Plug Type I (Australia) | | | | |
| 1 | Plastic Tool Case with Die Storage | | | | | | | |
| 1 | Tool Carrying Strap | | | | | | | |

CT-2931/CVTO Tool includes:

| Qty. | Description / Item |
|------|--|
| 1 | Battery Operated Hydraulic Crimp Tool with Dual-Layer PVC Head Cover |

Technical Information:

| Tool Weight (including battery) | 15.9 lbs. (7.2 kg) |
|---------------------------------|---|
| Dimensions (including battery) | 16.2" L x 12.6" H x 3.0" W [412 L x 319 H x 75 W] mm |
| Crimping Force | 12 tons (108 kN) |

Tools are to be used with Panduit crimp dies, and are sold separately. Go to www.panduit.com for more information.

A copy of the operation manual and accessory information can be found at: www.panduit.com.

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

| CT-2931/STCVINT, | CT-2931/STCV, CT-2 | | | |
|------------------|---------------------|--|--|--|
| • | CT-2931/ST | | | |
| | CT-2931/STCVAUS & | | | |
| ER DRAWING | CUSTOMER DR | | | |
| DANBUIT | ITEM REVISION NAME: | | | |
| | | | | |

| | | | | | | | CT-2931/STCVUK, CT-2931/STCVAUS & CT-2931/CVTO CUSTOMER DRAWING | |
|-----|---------|-----|-----|------|------------------|--------|---|--------------------------------|
| | | | | | | | ITEM REVISION NAME: 00084SLC_DC/00 | PANDUIT |
| | | | | | | | UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± (.xxx) ± | MATERIAL: |
| 00 | 7-25-16 | ВКА | ACC | JADE | DRAWING RELEASED | 010819 | (.xx) ± ANGLES ± THIRD ANGLE PROJECTION | DRAWING NUMBER: 00084SLC_DC |
| REV | DATE | ВҮ | СНК | APR | DESCRIPTION | ECN | BKA 7-21-16 CHK SCALE NONE | SHT 1 OF 1 SIZE B |