



NG4access® Cabled Module, singlemode LC/UPC to stub, 24 fiber, microcable, 61 m

- Cabled modules enable the routing of fiber cable to the frame, where multiple connectors are terminated to the frame with a single click
- Integrated connectors ensure the cables are kept in sequential order, and help prevent accidental fiber breakage or disruption to adjacent fibers during installation
- Available in a pigtail version for splicing on frame or preterminated to 24-fiber microcable or conventional IFC cable

## Product Classification

<b>Brand</b>	NG4access®
<b>Product Series</b>	NG4access
<b>Product Type</b>	Fiber cabled module
<b>Regional Availability</b>	Latin America   North America

## Construction Materials

<b>Fiber Type</b>	G.657.A2
<b>Fiber Mode</b>	Singlemode
<b>Total Fibers, quantity</b>	24

## Dimensions

<b>Cable Stub Length</b>	61 m   200 ft
<b>Depth</b>	92.71 mm   3.65 in
<b>Height</b>	13.21 mm   0.52 in
<b>Width</b>	159.77 mm   6.29 in

## Environmental Specifications

<b>Operating Temperature</b>	-5 °C to +40 °C (+23 °F to +104 °F)
<b>Relative Humidity</b>	Up to 85%, non-condensing
<b>Storage Temperature</b>	-5 °C to +50 °C (+23 °F to +122 °F)

## General Specifications

<b>Interface, front</b>	LC
<b>Total Ports, quantity, front</b>	24
<b>Interface Feature, front</b>	Standard
<b>Color, front</b>	Black
<b>Adapter Color</b>	Blue
<b>Adapters, quantity, front</b>	12

Application	For use with NG4 panels
Body Style	Duplex   Straight orientation
Cable Stub Type	Microcable
Color, housing	Black
Packaging Type	Bag   Carton
Polarity	Pairs, straight
Interface, rear	Stub tail
Adapters, quantity, rear	1
Color, rear	Black
Package Quantity	1

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant