



Part Number: GIMT206

Indoor Distribution 06 Fibers OM2

Product Description

Indoor Mini Breakout Tight Optical Cable 06 x 50/125-OM2 I-V(ZN)H

Technical Drawing

Fiber properties - EMEA

Introduction

This document provides technical data on the fibers used in Optical Fiber Cables produced in the EMEA region.

Optical Characteristics

Characteristics Single-Mode – Matched-Cladded optical fibers according to ITU

EMEA P/N Coding, Position 5	Fibre-Type	Mode-Field (Cladding) Diameter (µm)	Wave-length (nm)	Dispersion (ps/nm-km)	PMD ^A (ps.km)	Cable Cut-off Wave-length (nm)
7	9/125 G.655 C&D	8.4 ± 0.6 125 ± 0.7	1550 1625	≤ 4.5 ≤ 7.9	≤ 0.04	≤ 1260
8	9/125 G.652D & G.657A1 BI OS2	9.2 ± 0.4 125 ± 0.7	1310 1550 1625	≤ 3.2 ≤ 17	≤ 0.06	≤ 1260
A	9/125 G.657A1 BI	8.9 ± 0.4 125.0 ± 0.3	1310 1550 1625	≤ 3.5 ≤ 18	≤ 0.06	≤ 1260
F	9/125 G.657A2 BI	8.9 ± 0.4 124.8 ± 0.3	1310 1550 1625	≤ 3.5 ≤ 18	≤ 0.2	≤ 1260
I	9/125 G.657B3 BI	8.8 ± 0.4 125 ± 0.4	1310 1550 1625	≤ 3.5 ≤ 18	≤ 0.06	≤ 1260

Note A: Link design value

Characteristics Multi-Mode – Graded-Index optical fibers according to IEC 60793

EMEA P/N Coding, Position 5	Fibre-Type	Core/Cladding Diameter (µm)	Wave-length (nm)	Band-width (MHz.km)	Ethernet Performance (m)				Num. Apert. (µm)
					1 GBE	10 GBE	40 Gbps WDM	100 Gbps WDM	
1	62.5/125 OM1	62.5 ± 2.5 125 ± 1	850 1300	≥ 200 ≥ 600	220 550	33 300			0.275 ± 0.015
2	50/125 OM2 BI	50 ± 2.5 125 ± 1	850 1300	≥ 500 ≥ 500	600 600	63 300			0.20 ± 0.015
D	50/125 OM3 BI	50 ± 2.5 125 ± 1	850 1300	≥ 1500 ≥ 500	1000 550	300 300			0.20 ± 0.015
E	50/125 OM4 BI	50 ± 2.5 125 ± 1	850 1300	≥ 3500 ≥ 500	1100 550	550 300			0.20 ± 0.015
C	50/125 OM5 BI	50 ± 2.5 125 ± 1	850 1300	≥ 3500 ≥ 500			440	150	0.20 ± 0.015

Belden Technical Support +31 (0) 77 3875 414 www.belden-emea.com

©Copyright 2008, Belden Wire & Cable B.V. Netherlands • Tel. +31-(0)77-3875-555 • Fax +31-(0)77-3875-488 • E-mail: verko.salesinfo@belden.com
All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.
All printing errors are subject to correction. Technical specifications are subject to change without notice.

Technical Specifications

Product Overview

Construction Type:	Distribution
Environmental Space:	Indoor - Euroclass B2ca
Suitable Applications:	Structured (premises) wiring systems: building backbone (riser) and/or horizontal cabling (Fibre To The Desk). Support all computer network applications such as FDDI, Gigabit Ethernet and ATM

Construction

Fiber Cable Construction

Fiber Type	Fiber Count
OM2	6

Fiber Type:	OM2
Fiber Count:	6
Fiber Color Coding:	TIA coding (Gxxxxx.T): Blue, Orange, Green, Brown, Gray, White
Fiber Color Coding 2:	Europe coding (Gxxxxx.0): Red, Natural, Yellow, Blue, Green, Violet

Buffer Specification

Fiber Type	Buffer Construction	Buffer Material	Buffer Diameter
OM2	Tight	LSZH - Low Smoke Zero Halogen	0.9 mm

Bulk Cable Weight:	26 kg/km
--------------------	----------

Jacket Specifications

Number of Jackets:	Single Jacket
Type of Armor:	Non-Armored

Outer Jacket Material

Material	Nominal Diameter	Ripcord
LSZH - Low Smoke Zero Halogen	5.3 mm	0

Optical Characteristics

Fiber Core Diameter:	50 µm
Max Attenuation at 1300 nm:	1.0 dB/km
Max Attenuation at 850 nm:	2.9 dB/km

Mechanical Characteristics

Min Bend Radius During Installation:	106 mm
Min Bend Radius During Operation:	53 mm
Max Tensile Strength During Installation:	900 N (202 lbf)
Max Tensile Strength During Operation:	450 N (101 lbf)

Temperature Range

Operating Temp Range:	-5 °C to +55 °C
Installation Temp Range:	-5 °C to +50 °C
Storage Temp Range:	-30 °C to +70 °C

Tensile Strength

Max Tensile Strength During Inst - Test Standard:	IEC 60794-1-21-E1
Max Tensile Strength During Operation - Test Standard:	IEC 60794-1-21-E1

Standards

UL Rating/Flame Test:	Non-UL Rated
CPR Euroclass:	B2ca-s1a,d1,a1
REACH:	Compliant
ISO/IEC Compliance:	IEC 60794
EU Directive 2011/65/EU (ROHS II):	Compliant
UV/ Sunlight Protection:	yes

History

Variants

Item #	Color
GIMT206.002100	Orange
GIMT206.004100	Orange

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.