

MS2™ Super Mini Module Straight, Dry Transparent

The Corning logo is a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

CORNING

Part Number:**80610863070**

MS2™ Super Mini Module Dry Transparent 4000-D/TR/24 is a 25-pair straight splice module that features an array of U-shaped, phosphor-bronze contacts and stainless steel cut-off blades. This dry module with a transparent cover is designed for aerial, buried and underground applications. It is suggested to use one of the MS2™ Splicing Rigs along with this product.

MS2™ Super Mini Module Straight, Dry Transparent

CORNING

Specifications

Design

Composition	Dry
Pair Count	25
Sealing Type	Sealed
Connector Type	Straight
Closure Type	Sealed
Conductor	28 - 22 AWG

Mechanical Specifications

Connection	IDC
------------	-----

General Specifications

Product Type	Modules
Cable Type	PIC, Pulp, Paper

Dimensions

Length	164.5 mm (6.48 in)
Height	9.1

Standards

Flame Retardance	No
------------------	----

MS2™ Super Mini Module Straight, Dry Transparent

The Corning logo consists of the word "CORNING" in a white, serif, all-caps font, centered within a solid blue square.

Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.