

Line-Interactive UPS with USB and 8 Outlets - 120V, 1000VA, 600W, 50/60 Hz, AVR, ECO Series

MODEL NUMBER: ECO1000LCD



Line-interactive UPS provides energy-efficient battery backup with AVR protection for your desktop computer and home theater system.

Features

Energy-Saving 1000VA/600W USB Battery Backup for PCs or Home Theater Systems

This 120V line-interactive AVR UPS system provides reliable battery backup and AC power protection against blackouts, brownouts, surges and line noise that can damage valuable electronics or destroy data. The 8-outlet UPS is ideal protection for your home office or media center components, including computers, routers, printers, NAS drives, HDTVs, Blu-ray players, game consoles, media players, DVRs and audio receivers.

Allows Time to Back Up Critical Files During a Blackout

Backup support allows you to work through short power failures, and gives you enough time to safely save files and shut down your system in case of a prolonged blackout. Backup time varies according to load, but the line-interactive UPS system should keep an energy-efficient desktop computer with LCD monitor powered as long as 40 minutes. During normal operation, incoming utility power keeps the UPS battery fully charged, so backup power will always be available. The hot-swappable internal batteries can be replaced by the user.

Connects Your Equipment to 8 NEMA 5-15R Outlets

Four 5-15R outlets provide both battery backup and surge protection for your computer, monitor and other crucial components. The other four 5-15R outlets are surge-protected only for printers, scanners and other non-essential equipment. Four outlets—two battery/surge and two surge-only—are spaced apart from the others to accommodate bulky transformers. Three are ECO outlets designed to save you money and protect the environment (see below).

ENERGY STAR-Certified to Help You Save Money and Protect the Environment

By meeting strict EPA efficiency guidelines, this ENERGY STAR-certified UPS system helps you save money and energy. An ECO power-saving option features three ECO outlets—two surge-only, one surgeand battery-protected—that turn off automatically when the device connected to the Battery Backup Master Outlet is powered down or in sleep mode. These outlets are recommended for printers, desk lamps and other non-essential peripherals that don't need to be operational all the time.

Even Backs up Essential Data When You Aren't Around

Use the included USB cable to connect the USB-B port to your computer. Working with Tripp Lite's free downloadable PowerAlert® software, this optional feature can enable safe unattended system shutdown and file saves in the event of a prolonged power failure when you aren't around.

Automatic Voltage Regulation (AVR) Corrects Low-Voltage Conditions

AVR protects your equipment from incremental hardware damage, data loss and performance problems caused by brownouts. The ECO1000LCD can correct brownouts as low as 86V back to nominal 120V power without drawing on the battery backup needed to support your equipment during a blackout. **316 Joules Fight Back Against Unexpected Power Surges**

A 316-joule surge suppression rating protects connected components from the harmful effects of power

Highlights

- Protects valuable equipment from dangers posed by brownouts, surges and line noise
- Battery backup allows enough time to save files and safely shut down during blackouts
- 8 NEMA 5-15R outlets provide power to desktop PC or home theater systems
- Highly efficient UPS includes 3 ECO outlets, to help you save energy and money
- Easy-to-read digital display reports important UPS and power information in real time

Applications

- Protect your PC and other sensitive electronics against power surges, brownouts and blackouts
- Operate essential equipment during short-term power outages using battery backup power
- Shut down PCs, DVRs, routers and other equipment without data loss during long-term power outages
- Turn off outlets connected to printers, desk lamps and other non-essential devices when not in use to save energy

Package Includes

 ECO1000LCD ECO LCD 120V 1000VA 600W Line-Interactive UPS



surges. Dual network data line surge suppression jacks protect a wired peripheral from dangerous surges on a single 10/100Base-T or dial-up network connection.

USB Charging Ports Keep Mobile Devices Fully Powered for Immediate Use

Two 5V USB ports share 2.1 amps of maximum charge current for charging smartphones, tablets, MP3 players and other essential mobile devices compatible with USB chargers. These ports are intended only for USB charging, which is available when the UPS system is turned on and receiving utility power. **Combats Electromagnetic Interference That Can Harm Equipment**

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems and can lead to incremental hardware damage, data corruption and audio/video transmission problems. The ECO1000LCD incorporates technology that filters out disruptive line noise so that it won't affect your equipment.

Easy-to-Read LCD Reports Real-Time UPS and Power Status

The front-panel LCD displays a variety of UPS and site electrical conditions, including UPS operating mode, voltage, frequency, load level, battery charge level, wiring fault and estimated runtime remaining. A built-in audible alarm sounds to warn you of a low battery or overload conditions.

Tower Form Factor for Easy Placement in Your Workspace or Media Center

The long-lasting ABS housing fits easily on a desktop, shelf or anywhere else convenient to your workstation or home theater. The six-foot power cord connects to a properly grounded AC wall outlet. The right-angle NEMA 5-15P plug allows easier connection in tight spaces.

Specifications

OVERVIEW		
UPC Code	037332205148	
UPS Type	Line-Interactive	
INPUT		
Rated input current (Maximum Load)	12A	
Nominal Input Voltage(s) Supported	120V AC	
UPS Input Connection Type	5-15P	
Input Circuit Breakers	15A	
UPS Input Cord Length (ft.)	6	
UPS Input Cord Length (m)	1.8	
Recommended Electrical Service	15A 120V	
Input Phase	Single-Phase	
OUTPUT		
Output Volt Amp Capacity (VA)	1000	
Output kVA Capacity (kVA)	1.0	
Output Watt Capacity (Watts)	600	
Nominal Voltage Details	120v nominal output in battery mode	
Frequency Compatibility	50 / 60 Hz	
Frequency Compatibility Details	Automatic frequency selection	

- USB cable
- Owner's manual



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Output Voltage Regulation (Line Mode)	120V (+18% / -13%)		
Output Voltage Regulation (Battery Mode)	120V (±10%)		
UPS Output Receptacles (Surge Suppression Only)	4 UPS outlets, 4 surge-only outlets		
Output AC Waveform (AC Mode)	Sine wave		
Output AC Waveform (Battery Mode)	PWM sine wave		
Nominal Output Voltage(s) Supported	110V; 115V; 120V		
Output Receptacles	(8) 5-15R		
Individually Controllable Load Banks	No		
BATTERY			
Full Load Runtime (min.)	2 min. (600w)		
Half Load Runtime (min.)	7 min. (300w)		
DC System Voltage (VDC)	12		
Battery Recharge Rate (Included Batteries)	7 hours from 10% to 90%		
Internal UPS Replacement Battery Cartridge	<a class="productLink" href="//www.tripplite.com/UPS-Replacement-Battery-Cartridge-Tripp-Lite-APC-Belkin-
Best-Powerware-Liebert-other-UPS~RBC51">RBC51		
Expandable Runtime	No		
VOLTAGE REGULATION			
Voltage Regulation Description	Automatic voltage regulation (AVR) maintains line power operation during brownouts as low as 86V (60Hz operation) / 105V (50Hz operation)		
Undervoltage Correction	Input voltages between 86 and 105 are boosted by 23% (60Hz operation only)		
USER INTERFACE, ALERTS & CONTROLS			
Front Panel LCD Display	LCD screen offers detailed UPS status information, configuration options and error message reporting; STATUS INFORMATION input voltage, output voltage, input frequency, output frequency, load in VA, load in watts, battery charge level (4 bar graph), estimated runtime remaining (minutes) and UPS operating mode; CONFIGURATION OPTIONS Eco-mode off/on, alarm disable; ERROR MESSAGES Replace battery, overload and critical fault (see manual for complete listing)		
Switches	ON / OFF / TEST Button offers power control and self-test operation; MUTE Button enables alarm-cancel and silent- mode opeation; SELECT Button is used to toggle LCD condition displays		
Alarm Cancel Operation	Temporary alarm cancel and silent-mode operation is available using front-panel MUTE button (see manual)		
Audible Alarm	Audible alarm indicates low battery, fault, overload and replace battery condition warnings		
SURGE / NOISE SUPPRESSION			
UPS AC Suppression Joule Rating	316		
UPS AC Suppression Response Time	Instantaneous		



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

UPS Dataline Suppression	1 line TEL/DSL (1 in / 1 out); 10/100Base T Ethernet		
EMI / RFI AC Noise Suppression	Yes		
PHYSICAL			
Cooling Method	Convection		
Installation Form Factors Supported with Included Accessories	Tower		
Primary Form Factor	Tower		
Primary UPS Depth (mm)	288		
Primary UPS Height (mm)	279		
Primary UPS Width (mm)	99		
UPS Housing Material	ABS		
UPS Power Module Dimensions (hwd, in.)	11 x 3.9 x 11.33		
UPS Power Module Weight (kg)	8.35		
UPS Power Module Weight (lbs.)	18.4		
ENVIRONMENTAL			
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius		
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius		
Relative Humidity	Up to 95%, non-condensing		
AC Mode BTU / Hr. (Full Load)	98		
AC Mode Efficiency Rating (100% Load)	96%		
COMMUNICATIONS			
Network Monitoring Port Description	Supports detailed monitoring of UPS and site power conditions		
PowerAlert Software	For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at http://www.tripplite.com/poweralert		
Communications Cable	USB cable included		
WatchDog Compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications		
Communications Interface	USB (HID enabled)		
LINE / BATTERY TRANSFER			
Transfer Time	6 milliseconds		
Low Voltage Transfer to Battery Power (Setpoint)	86V during 60Hz operation (105V during 50Hz operation)		
High Voltage Transfer to Battery Power (Setpoint)	142V		



SPECIAL FEATURES		
Cold Start (Startup in Battery Mode During a Power Failure)	Yes	
High Availability UPS Features	Automatic Voltage Regulation (AVR); Surge/noise protection	
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS; Power saving auto-shutoff ECO outlets	
STANDARDS & COMPLIANCE		
UPS Certifications	ENERGY STAR Qualified; Meets FCC Part 15 Category B (EMI); Tested to CSA (Canada); Tested to NOM (Mexico); Tested to UL1778 (USA)	
UPS Certification Details	UL1778: 2014 5th EDITION; CAN/CSA-C22.2 NO. 107.3:2014 3rd EDITION	
WARRANTY		
Product Warranty Period (U.S. & Canada)	3-year limited warranty	
Product Warranty Period (Latin America)	3-year limited warranty	
Product Warranty Period (International)	2-year limited warranty	
Product Warranty Period (Mexico)	3-year limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 Ultimate Lifetime Insurance	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies