

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Cat6a 10G-Certified Snagless Shielded STP Ethernet Cable (RJ45 M/M), PoE, Gray, 15 ft.

MODEL NUMBER: N262-015-GY









Snagless Cat6a cable with Power over Ethernet (PoE) connects 10G equipment in your high-speed 10GBase-T network.

Features

High-Speed Cat6a STP Patch Cable Ideal for Your 10GBase-T Ethernet Network

Designed for fast transmission and excellent signal quality, this 15-foot Cat6a cable ensures peak performance throughout your local area network (LAN). It transmits 10 Gbps data, voice and video through high-speed 10G equipment, including network switches, modems, routers, adapters, hubs and patch panels. At 500 MHz, it reduces impedance and structural return loss compared to standard 100 MHz wire.

Supports Power over Ethernet to Save You Money and Give You More Installation Choices

Because this Cat6a shielded cable supports PoE, it can supply the power to operate compatible PoE devices, such as security cameras, VoIP telephones, point-of-sale kiosks and access control devices. This saves you the expense and effort of purchasing, connecting and installing individual power supplies for each device. It also helps you install PoE devices in areas far away from AC outlets, such as poles or ceilings.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. The N262-015-GY shields against disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Snagless RJ45 Male Connectors Add Extra Protection During Installation

The RJ45 connectors' snagless design protects the locking tabs from being damaged or broken off during installation. The ends are shielded to minimize near-end crosstalk (NEXT) levels. Integral strain relief gives the N262-015-GY extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

Highlights

- Cat6a STP patch cord rated for high-speed 10 Gbps communications
- Ideal for connecting 10G network switches, routers, hubs and other equipment
- Supports PoE to save you expense and effort of powering PoE devices individually
- Dispels EMI/RFI line noise that can destroy data and affect equipment performance
- Snagless RJ45 connectors prevent tabs from being damaged during installation

Applications

- Connect 10GBase-T networks or digital signage in a highdensity data center
- Deliver power to PoE devices mounted in areas that are difficult to reach or have no electrical outlets
- Replace an old or missing RJ45 cable
- Provide universal connectivity for LAN network components, such as switches, servers, modems, routers, adapters, VoIP phones, security cameras and point-of-sale kiosks

Package Includes

 N262-015-GY Cat6a 10G-Certified Snagless Shielded STP Ethernet Cable (RJ45 M/M), Gray, 15 ft.



Specifications

NPUT 15 15 16 16 16 16 16 16	-		
Storage Temperature Range	OVERVIEW		
Cable Length (ft.) 15 Cable Length (m) 4.6 Cable Length (m) 4.6 Cable Length (in.) 180 PHYSICAL Cable Jacket Rating CM Cable Jacket Rating STP Cable Jacket Rating STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wive Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps LEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 R, J45 (MALE) Side B - Connector 1 R, J45 (MALE) Contact Plating Gold	UPC Code	037332256829	
Cable Length (m) 4.6 Cable Length (in.) 180 PHYSICAL Cable Jacket Rating CM Cable Jacket Rating CM Cable Outer Diameter (OD) 6.2mm Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	INPUT		
Cable Length (in.) 180 PHYSICAL Cable Jacket Rating CM Cable Outer Diameter (OD) 6.2mm Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 80.3 at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Cable Length (ft.)	15	
Cable Jacket Rating CM Cable Outer Diameter (OD) 6.2mm Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Cable Length (m)	4.6	
Cable Jacket Rating CM Cable Outer Diameter (OD) 6.2mm Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 80.2.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Cable Length (in.)	180	
Cable Outer Diameter (OD) 6.2mm Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 80.2.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	PHYSICAL		
Cable Shielding STP Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Cable Jacket Rating	СМ	
Color Gray Material of Construction PVC Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Cable Outer Diameter (OD)	6.2mm	
PVC	Cable Shielding	STP	
Snagless Connector Yes Wire Gauge (AWG) 26 Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Color	Gray	
Wire Gauge (AWG) Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Material of Construction	PVC	
Wire Type Stranded ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Contact Plating Gold	Snagless Connector	Yes	
ENVIRONMENTAL Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Wire Gauge (AWG)	26	
Operating Temperature Range 14 to 122 F (-10 to 50 C) Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Wire Type	Stranded	
Storage Temperature Range 5 to 140 F (-15 to 60 C) Operating Humidity Range 0% to 90% RH, Non-Condesning Storage Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	ENVIRONMENTAL		
Operating Humidity Range 0% to 90% RH, Non-Condesning COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Operating Temperature Range	14 to 122 F (-10 to 50 C)	
COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Storage Temperature Range	5 to 140 F (-15 to 60 C)	
COMMUNICATIONS Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Operating Humidity Range	0% to 90% RH, Non-Condesning	
Network Speed 10Gbps IEEE Standards Supported 802.3at CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Storage Humidity Range	0% to 90% RH, Non-Condesning	
CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	COMMUNICATIONS		
CONNECTIONS Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	Network Speed	10Gbps	
Side A - Connector 1 RJ45 (MALE) Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	IEEE Standards Supported	802.3at	
Side B - Connector 1 RJ45 (MALE) Contact Plating Gold	CONNECTIONS		
Contact Plating Gold	Side A - Connector 1	RJ45 (MALE)	
	Side B - Connector 1	RJ45 (MALE)	
FEATURES & CRECIFICATIONS	Contact Plating	Gold	
FEATURES & SPECIFICATIONS			



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Technology	Cat6a
STANDARDS & COMPLIANCE	
OTANDANDO A COMIT ETANCE	
Certifications	RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies