according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2012 RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesives

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA

Address : Everslaan 45

3078 Everberg Belgium

Telephone : +41 61 299 20 41 Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P391 Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

1,4-Bis(2,3-epoxypropoxy)butane

Additional Labelling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concent
	EC-No.		ration

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

	Index-No. Registration number		(% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxir ane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 70 - < 90
1,4-Bis(2,3- epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1,100 mg/kg	>= 3 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

: Carbon oxides

products

Halogenated compounds

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006



Enriching lives through innovation

ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

Advice on common storage

: For incompatible materials please refer to Section 10 of this

SDS.

Further information on

storage stability

: Stable under normal conditions.

Recommended storage

temperature

: 2 - 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1- methylethylidene)bis(4, 1- phenyleneoxymethylen e)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m3
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
1,4-Bis(2,3- epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4.7 mg/m3
	Workers	Dermal	Long-term systemic effects	6.66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

2,2'-[(1-methylethyli phenyleneoxymethy ne		Fresh water	0.006 mg/l		
Remarks:	Assessme	Assessment Factors			
		Marine water	0.001 mg/l		
	Assessme	ent Factors	l		
		Fresh water sediment	0.341 mg/kg dry weight (d.w.)		
	Equilibriu	Equilibrium method			
_		Marine sediment	0.034 mg/kg dry weight (d.w.)		
	Equilibriu	m method			
		Soil	0.065 mg/kg dry weight (d.w.)		
	Equilibriu	m method	<u>'</u>		
	1	Sewage treatment plant	10 mg/l		
	Assessme	ent Factors	<u> </u>		
		Secondary Poisoning	11 mg/kg		
1,4-Bis(2,3-epoxypr	ropoxy)butane	Fresh water	0.024 mg/l		
	Assessme	ment Factors			
		Marine water	0.002 mg/l		
	Assessme	Assessment Factors			
		Sewage treatment plant	100 mg/l		
	Assessme	ent Factors	-		
		Fresh water sediment	0.084 mg/kg dry weight (d.w.)		
	Equilibriu	m method	1		
		Marine sediment	0.008 mg/kg dry weight (d.w.)		
	Equilibriu	Equilibrium method			
		Soil	0.003 mg/kg dry weight (d.w.)		
	Equilibriu	m method	,		
	-	Oral	0.028 mg/kg		

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

Hand protection

Material : butyl-rubber Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light yellow

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : 6 (20 °C)

Concentration: 500 g/l

Melting point/freezing point : No data is available on the product itself.

Boiling point : $> 200 \, ^{\circ}\text{C}$

Flash point : 204 °C

Method: Cleveland open cup

Evaporation rate : No data is available on the product itself.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : < 0.002 hPa (20 °C)

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.17 g/cm3 (25 °C)

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity

Viscosity, dynamic : 25,000 - 45,000 mPa.s (25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 400001008017 1.3 01.06.2021 Date of first issue: 03.08.2015

Print Date 20.07.2021

Conditions to avoid None known.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition carbon dioxide carbon monoxide products

Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity -

Product

: Acute toxicity estimate : > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity -

Product

: Acute toxicity estimate : > 2,000 mg/kg

Method: Calculation method

Acute toxicity (other routes of : No data available

administration)

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit Exposure time: 4 h

Assessment: Irritating to skin. Method: OECD Test Guideline 404

Result: Irritating to skin.

1,4-Bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Assessment: Irritating to eyes.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429

Result: The product is a skin sensitiser, sub-category 1B.

1,4-Bis(2,3-epoxypropoxy)butane:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

Components:

1,4-Bis(2,3-epoxypropoxy)butane:

Assessment: Harmful if inhaled.

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

: Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

1,4-Bis(2,3-epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay

Concentration: 10 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

: Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Concentration: 1 - 100 µg/L

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

: Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive GLP: no

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Test Type: in vivo assay

Test species: Mouse (male)

Cell type: Germ

Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test Test species: Rat (male) Cell type: Somatic

Application Route: Oral

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

1,4-Bis(2,3-epoxypropoxy)butane:

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Test species: Mouse (male)

Cell type: Somatic Application Route: Oral Exposure time: 4 d Dose: 187.5 - 750 mg/kg

Method: OECD Test Guideline 474

Result: negative GLP: yes

Test Type: unscheduled DNA synthesis assay

Test species: Rat Cell type: Liver cells Application Route: Oral

Method: OECD Test Guideline 486

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Result: negative

Components:

1,4-Bis(2,3-epoxypropoxy)butane:

Germ cell mutagenicity-

Assessment

: Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic

effects.

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male Application Route: Oral Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day Frequency of Treatment: 7 days/week

No observed adverse effect level: 15 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Mouse, male Application Route: Dermal Exposure time: 24 month(s)

Dose: 0, 0.1, 10, 100 mg/kg bw/day Frequency of Treatment: 3 days/week

No-observed-effect level: 0.1 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, female Application Route: Dermal Exposure time: 24 month(s)

Dose: 0.1, 100, 1000 mg/kg bw/day Frequency of Treatment: 5 days/week

No-observed-effect level: 100 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female Application Route: Oral Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day Frequency of Treatment: 7 days/week

No observed adverse effect level: 100 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, females

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Application Route: Oral Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day Frequency of Treatment: 7 days/week No-observed-effect level: 2 mg/kg bw/day Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Carcinogenicity - : No data available

Assessment

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: No-observed-effect level: 540

mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg

body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal : Species: Rabbit, female development : Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: No observed adverse effect level:

30 mg/kg body weight

Developmental Toxicity: No observed adverse effect level:

300 mg/kg body weight Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: No observed adverse effect level:

60 mg/kg body weight

Developmental Toxicity: No observed adverse effect level:

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: No observed adverse effect level:

180 mg/kg body weight

Developmental Toxicity: No observed adverse effect level: >

540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

1,4-Bis(2,3-epoxypropoxy)butane:

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0/30/100/300 mg/kg bw/day Duration of Single Treatment: 17 d

General Toxicity Maternal: No observed adverse effect level:

300 mg/kg body weight

Developmental Toxicity: No observed adverse effect level:

300 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Reproductive toxicity -

Assessment

: No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: oral (gavage)

Exposure time: 14 WeeksNumber of exposures: 7 d

Dose: 0, 50, 250, 1000 mg/kg/day Method: OECD Test Guideline 408

Species: Rat, male and female

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

NOAEL: >= 10 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 5 d

Dose: 0, 10, 100, 1000 mg/kg/day Method: OECD Test Guideline 411

Species: Mouse, male NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 3 d

Dose: 0, 1, 10, 100 mg/kg/day Method: OECD Test Guideline 411

1,4-Bis(2,3-epoxypropoxy)butane: Species: Rat, male and female

NOAEL: 200 mg/kg Application Route: Oral

Exposure time: 28 dNumber of exposures: daily

Dose: 25, 100, 200, 400 mg/kg Method: Subacute toxicity

Species: Rat, male and female

NOAEL: 263 mg/kg Application Route: Oral

Exposure time: 90 hNumber of exposures: daily

Dose: 0,30,100,300 mg/kg bw/day Method: OECD Test Guideline 408

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Components:

1,4-Bis(2,3-epoxypropoxy)butane:

Repeated dose toxicity - : Harmful if inhaled.

Assessment

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Experience with human exposure

General Information: No data available

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EC50 : 11 mg/l Exposure time: 72 h

> Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009

NOEC : 4.2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC: 0.3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,4-Bis(2,3-epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l

End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: no

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 75 mg/l

End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 160

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209

GLP: no

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)

pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)

pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

1,4-Bis(2,3-epoxypropoxy)butane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 43 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Test Type: aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 38 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301E

GLP: no

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane: Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117

1,4-Bis(2,3-epoxypropoxy)butane:

Partition coefficient: n- : log Pow: -0.269 (25 °C)

octanol/water pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445

environmental compartments 1,4-Bis(2,3-epoxypropoxy)butane:

Distribution among : Koc: 12.59

environmental compartments Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: Date of last issue: 21.01.2020 SDS Number: 400001008017 1.3 01.06.2021 Date of first issue: 03.08.2015

Print Date 20.07.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID : UN 3082

number

14.2 UN proper shipping : Environmentally hazardous substance, liquid, n.o.s.

: 9

: 9

name

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard

class(es)

14.4 Packing group : III

Miscellaneous

Packing instruction (cargo

aircraft)

: 964

Packing instruction : 964

(passenger aircraft)

IATA (Passenger)

Environmentally hazardous yes

IATA (Cargo)

Environmentally hazardous yes

IMDG

14.1 UN number or ID : UN 3082

number

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, 14.2 UN proper shipping

name N.O.S.

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard

class(es)

14.4 Packing group : 111 Labels 9 EmS Code F-A, S-F

14.5 Environmental hazards

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 400001008017 1.3 01.06.2021 Date of first issue: 03.08.2015

Print Date 20.07.2021

Marine pollutant : yes

ADR

14.1 UN number or ID : UN 3082

number

14.2 UN proper shipping : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard

class(es)

Labels

14.4 Packing group : 111 9

: 9

: 9

14.5 Environmental hazards

Environmentally hazardous : yes

RID

14.1 UN number or ID : UN 3082

number

name

14.2 UN proper shipping : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard

class(es)

14.4 Packing group : 111 Labels 9

14.5 Environmental hazards

Environmentally hazardous : yes

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

F2 **ENVIRONMENTAL**

HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

Version Revision Date: SDS Number: Date of last issue: 21.01.2020 1.3 01.06.2021 400001008017 Date of first issue: 03.08.2015

Print Date 20.07.2021

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006



ARALDITE® 2012 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.01.2020

 1.3
 01.06.2021
 400001008017
 Date of first issue: 03.08.2015

Print Date 20.07.2021

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method

Eye Irrit. 2 H319 Based on product data or assessment

Skin Sens. 1 H317 Calculation method Aquatic Chronic 2 H411 Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.