

Product Code: PC1003

Description: C14 to C13 IEC Lock Connector 3G 1.00mm² H05VV-F Cable Black - 1.5 Metre



General Information

Complete Powerlead Rating	10A/250V	
	C14 Connector	C13 IEC Lock Connector
Component Rating	10A 250V~	10A 250V~
Colour	Black	Black
Materials	Over Moulding Cover: PVC Pins: Brass Strip Housing: PBT	Terminal Housing, Handle: Nylon (PA66) Over Mould: PVC Lock Lever & Red button: Polycarbonate Terminal Caddy: Nylon, Terminal: Phosphor Bronze Spring: 0.35mm Spring Steel, Locking Blade: Steel
Cable Specification		
Cable Colour	Black	Insulation Material PVC (Colour Coded)
Number of Conductors	3	Insulation Wall Thickness (mm) 0.6mm
Conductor Cross Sectional Area	1.00mm ²	Insulation Elongation 150%
Number of Strands	32	Insulation Tensile Strength
Conductor Material	Bare Copper (99.97%)	Nominal Resistance 19.5 Ohm/Km
Jacket Material	PVC	Overall Cable Diameter 7.1mm
Jacket Wall Thickness	0.8mm	Bend Radius 35.5°
Jacket Elongation	150%	Rated Temperature -15 to +70°C
Additional Information		
Cable Hanking	None	
Lock Retention	>100N	
Features	Quick connect from single terminal Class I protection	
Standards	IEC /BS EN 60320-1:2015 (VDE File 40016055) IEC /BS EN 60320-3:2014 (VDE File 40016055) DIN EN 50525-2-11: 2012-01 (VDE File 40010839) BS EN 50525-2-11: 2011 (VDE File 40010839)	