



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE 572

SDS No. : 454059

V010.0

Revision: 23.04.2024

printing date: 24.04.2024

Replaces version from: 13.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 572

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

H319 Causes serious eye irritation.

Category 2

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H319 Causes serious eye irritation.

Supplemental informationContains: Linalool; Cinnamaldehyde **May produce an allergic reaction.****Precautionary statement:**

"***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

**Precautionary statement:
Response**

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration $\geq$ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):This mixture does not contain any substances in a concentration $\geq$ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Octan-1-ol 111-87-5 203-917-6 01-2119486978-10	10- 20 %	Eye Irrit. 2, H319 Aquatic Chronic 3, H412	dermal:ATE = 2.500 mg/kg	
Cumene hydroperoxide 80-15-9 201-254-7 01-2119475796-19	0,1- < 1 %	STOT RE 2, H373 Skin Corr. 1B, H314 Acute Tox. 2, Inhalation, H330 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Org. Perox. E, H242 STOT SE 3, H335	Eye Irrit. 2; H319; C 1 - < 3 % Skin Irrit. 2; H315; C 3 - < 10 % Eye Dam. 1; H318; C 3 - < 10 % STOT SE 3; H335; C $\geq$ 1 % Skin Corr. 1B; H314; C $\geq$ 10 % ===== dermal:ATE = 1.100 mg/kg	
Linalool 78-70-6 201-134-4 01-2119474016-42	0,1- < 1 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317		
Cinnamaldehyde 104-55-2 203-213-9	0,001- < 0,01 % (10 ppm- < 100 ppm)	Aquatic Chronic 3, H412 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317	Skin Sens. 1A; H317; C $\geq$ 0,01 %	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.**For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Anaerobic

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7 [Titanium dioxide, total inhalable]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [Titanium dioxide, respirable]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure LimitsValid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Fluorophlogopite (Mg ₃ K[AlF ₂ O(SiO ₃) ₃]) 12003-38-2 [FLUORIDE]		2,5	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [Titanium dioxide]		4	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [Titanium dioxide]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Octan-1-ol 111-87-5	aqua (freshwater)		0,1 mg/l				
Octan-1-ol 111-87-5	aqua (marine water)		0,01 mg/l				
Octan-1-ol 111-87-5	Soil				0,26 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sewage treatment plant (STP)		0,35 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Soil				0,0029 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (freshwater)		0,2 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (marine water)		0,02 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (intermittent releases)		2 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sediment (freshwater)				2,22 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sediment (marine water)				0,222 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Soil				0,327 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sewage treatment plant (STP)		> 10 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Octan-1-ol 111-87-5	Workers	inhalation	Long term exposure - systemic effects		176 mg/m3	
Octan-1-ol 111-87-5	Workers	inhalation	Long term exposure - local effects		106 mg/m3	
Octan-1-ol 111-87-5	Workers	dermal	Long term exposure - systemic effects		50 mg/kg	
Octan-1-ol 111-87-5	Workers	dermal	Long term exposure - local effects		0,190 mg/cm2	
Octan-1-ol 111-87-5	General population	inhalation	Long term exposure - systemic effects		43,5 mg/m3	
Octan-1-ol 111-87-5	General population	dermal	Long term exposure - systemic effects		25 mg/kg	
Octan-1-ol 111-87-5	General population	dermal	Long term exposure - local effects		0,067 mg/cm2	
Octan-1-ol 111-87-5	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	inhalation	Acute/short term exposure - systemic effects		16,5 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	inhalation	Long term exposure - systemic effects		2,8 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	inhalation	Acute/short term exposure - systemic effects		4,1 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	oral	Acute/short term exposure - systemic effects		1,2 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	dermal	Acute/short term exposure - systemic effects		2,5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	dermal	Long term exposure - systemic effects		1,25 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	inhalation	Long term exposure - systemic effects		0,7 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	oral	Long term exposure - systemic effects		0,2 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	dermal	Long term exposure - local effects		1,5 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	dermal	Long term exposure - local effects		3 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	Workers	dermal	Acute/short term exposure - local effects		3 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6-78-70-6	General population	dermal	Acute/short term exposure - local effects		1,5 mg/cm2	

			effects			
Cinnamaldehyde 104-55-2	Workers	inhalation	Long term exposure - systemic effects		13,6 mg/m ³	
Cinnamaldehyde 104-55-2	Workers	dermal	Long term exposure - systemic effects		3,85 mg/kg	
Cinnamaldehyde 104-55-2	General population	inhalation	Long term exposure - systemic effects		2,4 mg/m ³	
Cinnamaldehyde 104-55-2	General population	dermal	Long term exposure - systemic effects		1,37 mg/kg	
Cinnamaldehyde 104-55-2	General population	oral	Long term exposure - systemic effects		1,37 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid, paste
Colour	white
Odor	mild, Acrylic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< -30 °C (< -22 °F)
Initial boiling point	> 150 °C (> 302 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	> 100 °C (> 212 °F); no method / method unknown
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-polar/aprotic.
Viscosity (kinematic) (40 °C (104 °F);)	> 20,5 mm ² /s
Solubility (qualitative) (Solvent: Acetone)	Soluble
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Slight
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure (20 °C (68 °F))	< 0,13 mbar
Density (20 °C (68 °F))	1,10 g/cm ³
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.
Acids.
Reducing agents.
Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.
Hydrocarbons
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information**General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Octan-1-ol 111-87-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Cumene hydroperoxide 80-15-9	LD50	382 mg/kg	rat	other guideline:
Linalool 78-70-6	LD50	2.790 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Cinnamaldehyde 104-55-2	LD50	2.220 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Octan-1-ol 111-87-5	LD50	2.000 - 4.000 mg/kg	rabbit	
Octan-1-ol 111-87-5	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Cumene hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
Linalool 78-70-6	LD50	5.610 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Cinnamaldehyde 104-55-2	LD50	1.260 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LC50	1,370 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Octan-1-ol 111-87-5	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Linalool 78-70-6	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cinnamaldehyde 104-55-2	Category 2 (irritant)		human	Patch Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Octan-1-ol 111-87-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Linalool 78-70-6	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Cinnamaldehyde 104-55-2	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Octan-1-ol 111-87-5	not sensitising	Draize Test	guinea pig	Draize Test
Linalool 78-70-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Cinnamaldehyde 104-55-2	Sub-Category 1A (sensitising)	Mouse local lymphnode assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Octan-1-ol 111-87-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Octan-1-ol 111-87-5	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Linalool 78-70-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Linalool 78-70-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Linalool 78-70-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Cinnamaldehyde 104-55-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
Octan-1-ol 111-87-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Linalool 78-70-6	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Linalool 78-70-6	NOAEL P 365 mg/kg NOAEL F1 365 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Octan-1-ol 111-87-5	NOAEL 1.000 mg/kg	dermal	90 d 6 h/d, 5 d/w	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
Linalool 78-70-6	NOAEL 117 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Cinnamaldehyde 104-55-2	NOAEL 275 mg/kg	oral: feed	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Cinnamaldehyde 104-55-2	NOAEL 300 mg/kg	oral: feed	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octan-1-ol 111-87-5	LC50	13,3 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Linalool 78-70-6	LC50	27,8 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cinnamaldehyde 104-55-2	LC50	2,35 mg/l	96 h	Danio rerio	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octan-1-ol 111-87-5	EC50	47 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	EC50	18,84 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Linalool 78-70-6	EC50	59 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cinnamaldehyde 104-55-2	EC50	3,21 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octan-1-ol 111-87-5	NOEC	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octan-1-ol 111-87-5	EC10	4,2 mg/l	48 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
Octan-1-ol 111-87-5	EC50	14 mg/l	48 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
Cumene hydroperoxide 80-15-9	EC50	3,1 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	NOEC	1 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Linalool 78-70-6	EC50	88,3 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Linalool 78-70-6	EC10	38,4 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cinnamaldehyde 104-55-2	EC50	31,6 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Octan-1-ol 111-87-5	EC 50	350 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	30 min	not specified	not specified
Linalool 78-70-6	EC0	100 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Cinnamaldehyde 104-55-2	NOEC	132 mg/l	16 h		not specified

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Octan-1-ol 111-87-5	readily biodegradable	aerobic	92 %	28 d	OECD Guideline 310 (Ready Biodegradability/CO2 in Sealed Vessels (Headspace Test))
Cumene hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Linalool 78-70-6	readily biodegradable	aerobic	> 97,1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Linalool 78-70-6	inherently biodegradable		100 %	13 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Cinnamaldehyde 104-55-2	readily biodegradable	aerobic	100 %	21 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Cumene hydroperoxide 80-15-9	9,1			calculation	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Octan-1-ol 111-87-5	3,5	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9	1,6	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Linalool 78-70-6	3,1	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Cinnamaldehyde 104-55-2	2,107	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Octan-1-ol 111-87-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide 80-15-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Linalool 78-70-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content	< 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.