

Product data sheet

Specifications



APC Back-UPS 850VA, 120V, 2 USB charging ports, 9 NEMA outlets (3 surge)

BE850G2

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	450 W
Rated power in VA	850 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R 3 NEMA 5-15R surge
Cable length	5 ft (1.5 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual USB cable
Range of Product	Back-UPS

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
Battery Charge Power (Watts)	13 W rated
Battery power in VAh	104 VAh runtime
Battery life	2...5 year(s)
Replacement battery	RBC17
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

color	Black
Height	5.5 in (139 mm)
Width	12.9 in (327 mm)
Depth	4.1 in (105 mm)
Net Weight	9.04 lb(US) (4.1 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

Output

Max Configurable Power (Watts)	450 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	850 VA
Transfer Time	6ms typical : 10ms maximum

Conformance

Product Certifications	California (CEC) Battery Charger cTUVus
------------------------	--

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	10...90 %
Storage altitude	0...5000 ft (0...1524 m)
Acoustic level	45 dBA
Heat dissipation	19.249 Btu/h

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault

Surge Protection and Filtering

Surge energy rating	354 J
---------------------	-------

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304413592
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.7 in (19.6 cm)
Package 1 Width	6.6 in (16.8 cm)
Package 1 Length	16.4 in (41.6 cm)
Package weight(Lbs)	9.7 lb(US) (4.4 kg)
SCC14	10731304413599
Pallet layers	16

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

D7202d15-7cd4-470e-bd06-f47695f20bd8

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)


Removable battery

User replaceable

Take-back

Yes

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Power certainty in a connected world



APC Back-UPS provide consistent, clean power to your electronics

so your devices perform better, last longer and stay connected during power outages.

Offer Marketing Illustration

Product benefits / Features



The image shows a black APC Back-UPS BE850G2 device. To its left, the text reads "Life Is On | Schneider Electric" and "APC". Below this, it says "APC Back-UPS" and "Reliable battery backup to keep you connected during prolonged power outages". At the bottom, five icons in green circles represent features: a battery for "Long battery runtime", a lightning bolt in a shield for "Reliable surge protection", a power outlet for "9 outlets", a leaf for "Lightweight design", and a USB symbol for "2 USB Charging Port".

Life Is On | Schneider Electric

APC

APC Back-UPS

Reliable battery backup to keep you connected during prolonged power outages

- Long battery runtime
- Reliable surge protection
- 9 outlets
- Lightweight design
- 2 USB Charging Port

Offer Marketing Illustration

Product benefits / Features



Power goes out. You stay connected to what matters

Enjoy uninterrupted internet connection for your entertainment, smart home and security devices.

Offer Marketing Illustration

Product benefits / Features



Robust battery to keep you on track

Reliable runtime allows you to continue digital activities when the power is out.

Image of product / Alternate images

Alternative

