



Part Number: FXU Frame OS2 06P

FX Ultra Frame OS2 6 Ports

Product Description

FX Ultra Frame OS2 6 Ports. Available in several fiber connector types.

Technical Specifications

Product Overview

Environmental Space:	Indoor	
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers	

Construction

Fiber Cable Construction

Fiber Type
OS2

Fiber Type:	OS2	

Buffer Specification

Fiber	Type
OS2	

Weight:	4.46 kg
Height:	1.5 m
Depth:	2.2

Temperature Range

Operating Temp Range:	-10 to 60°C
Storage Temp Range:	-10 to 75°C

Product Material

Materials

Description	Material	Color
Frame	Plastic - UL94V-0	Black
Front Connector Body	Plastic - UL94V-0	Blue

Standards

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-01-07
MII Order #39 (China RoHS):	EUP 50

Additional Notes

Packaging:	Individually packaged in a plastic shell, Shipped in cardboard box (60/box)
Included Parts:	Dust Caps
Related Parts:	FiberExpress Ultra Patch panels, Pre-terminated MPO low loss cable assemblies

History

Variants

Item #	Color	Connector Type	Port Count
FFSU06ST	Blue	ST	6 Port
FFSU06SD	Blue	SC Duplex	6 Port
FFSU06SB	Blue	SC/APC Simplex	6 Port
FFSU06SA	Blue	SC/APC Duplex	6 Port
FFSU06MP	Blue	MPO Up/Down	6 Port
FFSU06LKY	Blue	LC Keyed Yellow	6 Port
FFSU06LKW	Blue	LC Keyed White	6 Port
FFSU06LKV	Blue	LC Keyed Violet	6 Port
FFSU06LKS	Blue	LC Keyed Gray	6 Port
FFSU06LKR	Blue	LC Keyed Red	6 Port
FFSU06LKP	Blue	LC Keyed Rose	6 Port
FFSU06LKO	Blue	LC Keyed Orange	6 Port
FFSU06LKN	Blue	LC Keyed Black	6 Port
FFSU06LKM	Blue	LC Keyed Brown	6 Port
FFSU06LKG	Blue	LC Keyed Green	6 Port
FFSU06LKB	Blue	LC Keyed Blue	6 Port
FFSU06LKA	Blue	LC Keyed Aqua	6 Port
FFSU06LA	Blue	LC/APC Duplex	6 Port

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.